

## Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	AUREA 8	Reg. No.	012-SC1490-17	
Certificate Holder	Certificate Holder			
Name	Groupe Atlantic	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000	
City	La Roche Sur Yon	Country	France	
Certification Body	RISE CERT	RISE CERT		
Name of testing laboratory	RISE			
Subtype title	AUREA 8	AUREA 8		
Heat Pump Type	Outdoor Air/Water			
Refrigerant	R410a			
Mass Of Refrigerant	1.72 kg			



## **Model: AUREA 8**

General Data	
Power supply	1x230V 50Hz

## Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	7.90 kW	7.70 kW	
El input	1.75 kW	2.78 kW	
СОР	4.52	2.76	
Indoor water flow rate	1.39 m³/h	0.85 m³/h	

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

## **Average Climate**



 $$\operatorname{\textit{Page}}\xspace$  3 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	0 dB(A)	0 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825		
	Low temperature	Medium temperature
$\eta_{s}$	162 %	123 %
Prated	7.00 kW	6.20 kW
SCOP	4.13	3.15
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.19 kW	5.48 kW
COP Tj = -7°C	2.80	1.85
Pdh Tj = +2°C	3.77 kW	3.34 kW
COP Tj = +2°C	3.97	3.22
Pdh Tj = +7°C	2.80 kW	2.63 kW
COP Tj = +7°C	5.90	4.13
Pdh Tj = 12°C	3.03 kW	3.15 kW
COP Tj = 12°C	6.32	5.91
Pdh Tj = Tbiv	6.19 kW	5.48 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}$4$ of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$ 

COP Tj = Tbiv	2.80	1.85
Pdh Tj = TOL	5.83 kW	4.71 kW
COP Tj = TOL	2.57	1.59
Cdh	0.87	0.92
WTOL	55 °C	55 °C
Poff	5 W	5 W
РТО	60 W	50 W
PSB	5 W	5 W
PCK	0 W	o w
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	1.20 kW	1.50 kW
Annual energy consumption Qhe	3505 kWh	4068 kWh