

$$\operatorname{\textit{Page}}\ 1$$ of 4 This information was generated by the HP KEYMARK database on 27 Jan 2021

Summary of	AquaMaster Inverter AQ22I	Reg. No.	037-0062-21
Certificate Holder			
Name	Master Therm tepelna cerpadla s.r.o.		
Address	Vaclavske namesti 819/43	Zip	110 00
City	Praha	Country	Czech Republic
Certification Body	SZU - Strojirensky zkusebni ustav (Engineering Test Institute, Public Enterprise)		
Subtype title	AquaMaster Inverter AQ22I		
Heat Pump Type	Brine/Water		
Refrigerant	R32		
Mass Of Refrigerant	1 kg		
Certification Date	26.01.2021		
Testing basis	HP Keymark scheme rules rev. no. 7		

This information was generated by the HP KEYMARK database on 27 Jan 2021

Model: AquaMaster Inverter AQ22I

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	4.18 kW	3.81 kW	
El input	0.90 kW	1.32 kW	
СОР	4.66	2.89	
Indoor water flow rate	0.72 m³/h	0.41 m³/h	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

Average Climate



This information was generated by the HP KEYMARK database on 27 Jan 2021

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	45 dB(A)	45 dB(A)

	EN 14825	
	Low temperature	Medium temperature
η_{s}	208 %	152 %
Prated	7.08 kW	5.91 kW
SCOP	5.39	4.01
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	6.39 kW	5.27 kW
COP Tj = -7°C	4.12	2.96
Cdh	0.90	0.90
Pdh Tj = +2°C	3.54 kW	3.37 kW
COP Tj = +2°C	5.51	4.02
Cdh	0.90	0.90
Pdh Tj = +7°C	2.45 kW	2.12 kW
$COP Tj = +7^{\circ}C$	6.28	4.87
Cdh	0.90	0.90
Pdh Tj = 12°C	1.16 kW	1.07 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 27 Jan 2021

COP Tj = 12°C	6.37	5.02
Cdh	0.90	0.94
Pdh Tj = Tbiv	7.08 kW	5.91 kW
COP Tj = Tbiv	4.00	2.67
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.08 kW	5.91 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.00	2.67
WTOL	60 °C	60 °C
Poff	12 W	12 W
РТО	12 W	12 W
PSB	12 W	12 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2713 kWh	3051 kWh