

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	Alféa Hybrid Duo Gaz R6	Reg. No.	012-020
Certificate Holder			
Name	Groupe Atlantic	Groupe Atlantic	
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT	RISE CERT	
Name of testing laboratory	SP		
Subtype title	Alféa Hybrid Duo Gaz R6		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water	
Refrigerant	R410a		
Mass Of Refrigerant	1.1 kg		



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: Alféa Hybrid Duo Gaz R6

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	5.90 kW	4.50 kW	
El input	1.35 kW	1.79 kW	
СОР	4.37	2.51	
Indoor water flow rate	1.01 m³/h	0.49 m³/h	

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	46 dB(A)	46 dB(A)
Sound power level outdoor	63 dB(A)	63 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_{s}	169 %	115 %
Prated	5.00 kW	5.00 kW
SCOP	4.30	2.95
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	4.60 kW	4.00 kW
COP Tj = -7°C	2.70	1.80
Pdh Tj = +2°C	2.80 kW	2.50 kW
COP Tj = +2°C	4.20	2.90
Pdh Tj = +7°C	2.30 kW	1.70 kW
COP Tj = +7°C	6.00	4.00
Pdh Tj = 12°C	2.30 kW	2.10 kW
COP Tj = 12°C	8.30	5.80
Pdh Tj = Tbiv	4.60 kW	4.00 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}4 of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$

COP Tj = Tbiv	2.70	1.80
Pdh Tj = TOL	4.50 kW	3.50 kW
COP Tj = TOL	2.60	1.60
Cdh	0.90	0.90
WTOL	80 °C	80 °C
Poff	6 W	6 W
РТО	23 W	16 W
PSB	10 W	10 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Gas	Gas
Supplementary Heater: PSUP	0.70 kW	1.00 kW
Annual energy consumption Qhe	2505 kWh	3180 kWh