

#### Page 1 of 4 This information was generated by the HP KEYMARK database on 22 Jun 2022

#### **Login**

Summary of	Thermastage Silent Combi TSC14/ TOC14RIY	Reg. No.	012-C700095
Certificate Holder			
Name	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT		
Subtype title	Thermastage Silent Combi TSC14/ TOC14RIY		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410A		
Mass of Refrigerant	3.8 kg		
Certification Date	22.12.2020		
Testing basis	HP Keymark Scheme 2018		



This information was generated by the HP KEYMARK database on 22 Jun 2022

# **Model: Silent Combi TSC14/ TOC14RIY**

Configure model			
Model name	Silent Combi TSC14/ TOC14RIY		
Application	Heating (medium temp)		
Units	Indoor + Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply 1x230V 50Hz		

## Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	16.46 kW	14.86 kW	
El input	3.94 kW	5.65 kW	
СОР	4.18	2.63	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Shatting on the heat transfer medium now	passeu	
Complete power supply failure	passed	
Defrost test	passed	

## **Average Climate**



This information was generated by the HP KEYMARK database on 22 Jun 2022

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	45 dB(A)	45 dB(A)
Sound power level outdoor	67 dB(A)	67 dB(A)

EN 14825		
	Low temperature	Medium temperature
$\eta_{s}$	163 %	125 %
Prated	16.00 kW	14.00 kW
SCOP	4.15	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = $-7^{\circ}$ C	14.20 kW	12.00 kW
COP Tj = $-7^{\circ}$ C	2.79	1.98
Pdh Tj = $+2$ °C	8.70 kW	7.30 kW
COP Tj = +2°C	4.17	3.15
Pdh Tj = $+7^{\circ}$ C	7.00 kW	6.30 kW
COP Tj = +7°C	5.34	4.30
Pdh Tj = 12°C	8.10 kW	7.60 kW
COP Tj = 12°C	6.76	5.99
Pdh Tj = Tbiv	14.20 kW	12.00 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



### Page 4 of 4 This information was generated by the HP KEYMARK database on 22 Jun 2022

COP Tj = Tbiv	2.79	1.98
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	14.10 kW	10.60 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.54	1.75
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.92	0.96
WTOL	65 °C	65 °C
Poff	19 W	19 W
РТО	100 W	46 W
PSB	23 W	23 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.00 kW	3.00 kW
Annual energy consumption Qhe	8014 kWh	8757 kWh