

Page 1 of 10

This information was generated by the HP KEYMARK database on 18 Mar 2022

Login

Summary of	TERRA 6 HPLB	Reg. No.	011-1W0415		
Certificate Holder					
Name	Ochsner Wärmepumpen Gmb	Ochsner Wärmepumpen GmbH			
Address	Krackowizerstraße 4	Krackowizerstraße 4 Zip 4020			
City	Linz	Country	Austria		
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH				
Subtype title	TERRA 6 HPLB				
Heat Pump Type	Brine/Water				
Refrigerant	R410A				
Mass of Refrigerant	1.4 kg				
Certification Date	30.09.2020	30.09.2020			
Testing basis	HP KEYMARK certification scheme rules rev. 7				



Model: TERRA 6 HPLB, AVERAGE CLIMATE

Configure model		
Model name	TERRA 6 HPLB, AVERAGE CLIMATE	
Application	Heating (medium temp)	
Units	Indoor	
Climate Zone	n/a	
Reversibility	No	
Cooling mode application (optional)	n/a	

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	5.89 kW	5.26 kW
El input	1.23 kW	1.80 kW
СОР	4.80	2.92

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate



EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	46 dB(A)	46 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_{s}	201 %	137 %
Prated	6.00 kW	5.00 kW
SCOP	5.22	3.63
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7° C	5.90 kW	5.30 kW
$COPTj = -7^{\circ}C$	4.84	3.05
Cdh Tj = -7 °C		
Pdh Tj = +2°C	6.00 kW	5.50 kW
COP Tj = +2°C	5.16	3.58
Cdh Tj = +2 °C		
Pdh Tj = $+7^{\circ}$ C	6.00 kW	5.70 kW
COP Tj = +7°C	5.48	3.98
Cdh Tj = +7 °C		
Pdh Tj = 12°C	6.10 kW	5.80 kW



Page 4 of 10

This information was generated by the HP KEYMARK database on 18 Mar 2022

COP Tj = 12°C	5.84	4.45
Cdh Tj = +12 °C		
Pdh Tj = Tbiv	5.90 kW	5.30 kW
COP Tj = Tbiv	4.78	2.92
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW	5.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.78	2.92
WTOL	60 °C	60 °C
Poff	o w	0 W
РТО	55 W	55 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2326 kWh	2990 kWh



Model: TERRA 6 HPLB, low temperature, all climates

Configure model		
Model name	TERRA 6 HPLB, low temperature, all climates	
Application	Heating (low temp)	
Units	Indoor	
Climate Zone	Colder Climate + Warmer Climate	
Reversibility	No	
Cooling mode application (optional)	n/a	

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2		
	Low temperature	
Heat output	5.89 kW	
El input	1.23 kW	
СОР	4.80	

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate



EN 14825	
	Low temperature
η_{s}	201 %
Prated	6.00 kW
SCOP	5.22
Tbiv	-10 °C
TOL	-10 °C
Pdh Tj = -7 °C	5.90 kW
$COP Tj = -7^{\circ}C$	4.84
Cdh Tj = -7 °C	
Pdh Tj = $+2$ °C	6.00 kW
COP Tj = +2°C	5.16
Cdh Tj = +2 °C	
Pdh Tj = $+7^{\circ}$ C	6.00 kW
$COPTj = +7^{\circ}C$	5.48
Cdh Tj = +7 °C	
Pdh Tj = 12°C	6.10 kW
COP Tj = 12°C	5.84
Cdh Tj = +12 °C	
Pdh Tj = Tbiv	5.90 kW
COP Tj = Tbiv	4.78
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW





COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.78
WTOL	60 °C
Poff	o w
РТО	55 W
PSB	10 W
PCK	o w
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	2326 kWh

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)

Warmer Climate

EN 14825	
	Low temperature
η_{s}	199 %
Prated	6.00 kW
SCOP	4.90
Tbiv	2 °C





TOL	2 °C
Pdh Tj = +2°C	5.90 kW
COP Tj = +2°C	4.78
Cdh Tj = +2 °C	
Pdh Tj = +7°C	5.90 kW
$COP Tj = +7^{\circ}C$	5.09
Cdh Tj = +7 °C	
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	5.60
Cdh Tj = +12 °C	
Pdh Tj = Tbiv	5.90 kW
COP Tj = Tbiv	4.78
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.78
WTOL	60 °C
Poff	0 W
РТО	55 W
PSB	10 W
РСК	0 W
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	0.00 kW
	·




Annual energy consumption Qhe	1517 kWh
-------------------------------	----------

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)

Colder Climate

EN 14825	
	Low temperature
η_{s}	207 %
Prated	7.00 kW
SCOP	5.11
Tbiv	-15 °C
TOL	-22 °C
Pdh Tj = -7°C	6.00 kW
COP Tj = -7°C	5.33
Cdh Tj = -7 °C	
Pdh Tj = +2°C	6.00 kW
COP Tj = +2°C	5.58
Cdh Tj = +2 °C	
Pdh Tj = +7°C	6.10 kW
	1





 $$\operatorname{Page}\ 10$$ of 10 This information was generated by the HP KEYMARK database on 18 Mar 2022

$COP Tj = +7^{\circ}C$	5.79
Cdh Tj = +7 °C	
Pdh Tj = 12°C	6.10 kW
COP Tj = 12°C	5.52
Cdh Tj = +12 °C	
Pdh Tj = Tbiv	6.00 kW
COP Tj = Tbiv	5.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	5.22
WTOL	60 °C
Poff	o w
РТО	55 W
PSB	10 W
PCK	0 W
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	1.44 kW
Annual energy consumption Qhe	3362 kWh

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)