

This information was generated by the HP KEYMARK database on 23 Jun 2022

[Login](#)

Summary of	DAIKIN ALTHERMA 3 H HT ECH2O 14-18kW (300L)	Reg. No.	011-1W0524
Certificate Holder			
Name	DAIKIN Europe N.V.		
Address	Zandvoordestraat 300	Zip	B-8400
City	Oostende	Country	Belgium
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	DAIKIN ALTHERMA 3 H HT ECH2O 14-18kW (300L)		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	4.2 kg		
Certification Date	24.03.2022		
Testing basis	HP KEYMARK certification scheme rules rev. 9		

## Model: EPRA14DV3 / ETSH16P30E

### Configure model

Model name	EPRA14DV3 / ETSH16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	5.69 kW	7.24 kW
El input	1.22 kW	2.41 kW
COP	4.67	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.99
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1038 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	177 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.51	3.58
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5726 kWh	7211 kWh

## Domestic Hot Water (DHW)

### Average Climate

This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DW1 / ETSH16P30E

### Configure model

Model name	EPRA14DW1 / ETSH16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	5.90 kW	7.24 kW
El input	1.23 kW	2.47 kW
COP	4.79	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling



**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.87
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1069 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	186 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.71	3.57
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5479 kWh	7236 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DV3 / ETSHB16P30E

### Configure model

Model name	EPRA14DV3 / ETSHB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	5.69 kW	7.24 kW
El input	1.22 kW	2.41 kW
COP	4.67	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.99
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1038 kWh

## Average Climate



### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	177 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.51	3.58
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5726 kWh	7211 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DW1 / ETSHB16P30E

### Configure model

Model name	EPRA14DW1 / ETSHB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	5.90 kW	7.24 kW
El input	1.23 kW	2.47 kW
COP	4.79	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

## EN 14511-2

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

## EN 14825

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.87
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1069 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	186 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.71	3.57
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5479 kWh	7236 kWh

## Domestic Hot Water (DHW)

### Average Climate



<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DV3 / ETSX16P30E

Configure model	
Model name	EPRA14DV3 / ETSX16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

General Data	
Power supply	1x230V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	5.69 kW	7.24 kW
El input	1.22 kW	2.41 kW
COP	4.67	3.01

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.99
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1038 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	180 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.57	3.62
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5649 kWh	7134 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DW1 / ETSX16P30E

Configure model	
Model name	EPRA14DW1 / ETSX16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

General Data	
Power supply	3x400V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	5.90 kW	7.24 kW
El input	1.23 kW	2.47 kW
COP	4.79	2.93

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling



**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.87
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1069 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	190 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.81	3.63
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5366 kWh	7122 kWh

## Domestic Hot Water (DHW)

### Average Climate

This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DV3 / ETSXB16P30E

### Configure model

Model name	EPRA14DV3 / ETSXB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	5.69 kW	7.24 kW
El input	1.22 kW	2.41 kW
COP	4.67	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.99
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1038 kWh

## Average Climate



### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	180 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.57	3.62
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5649 kWh	7134 kWh

## Domestic Hot Water (DHW)

### Average Climate

This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA14DW1 / ETSXB16P30E

Configure model	
Model name	EPRA14DW1 / ETSXB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

General Data	
Power supply	3x400V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	5.90 kW	7.24 kW
El input	1.23 kW	2.47 kW
COP	4.79	2.93

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.56 kW
Cooling capacity	6.90
EER	2.7

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	6.9 kW
SEER	3.87
P <sub>dc</sub> T <sub>j</sub> = 35°C	6.90 kW
EER T <sub>j</sub> = 35°C	2.70
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.23 kW
EER T <sub>j</sub> = 30°C	3.65
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.05 kW
EER T <sub>j</sub> = 25°C	4.58
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	4.94 kW
EER T <sub>j</sub> = 20°C	5.41
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1069 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	190 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.81	3.63
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5366 kWh	7122 kWh

## Domestic Hot Water (DHW)

### Average Climate



This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DV3 / ETSH16P30E

Configure model	
Model name	EPRA16DV3 / ETSH16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	4.08
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1158 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	177 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.51	3.58
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5726 kWh	7211 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DW1 / ETSH16P30E

Configure model	
Model name	EPRA16DW1 / ETSH16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	3x400V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling



**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	3.98
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1188 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	186 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.71	3.57
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5479 kWh	7236 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DV3 / ETSHB16P30E

### Configure model

Model name	EPRA16DV3 / ETSHB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	4.08
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1158 kWh

## Average Climate



### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	177 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.51	3.58
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5726 kWh	7211 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DW1 / ETSHB16P30E

### Configure model

Model name	EPRA16DW1 / ETSHB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

## EN 14511-2

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

## EN 14825

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	3.98
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1188 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	186 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.71	3.57
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5479 kWh	7236 kWh

## Domestic Hot Water (DHW)

### Average Climate



This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DV3 / ETSX16P30E

### Configure model

Model name	EPRA16DV3 / ETSX16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	4.08
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1158 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	180 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.57	3.62
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5649 kWh	7134 kWh

## Domestic Hot Water (DHW)

### Average Climate

This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DW1 / ETSX16P30E

Configure model	
Model name	EPRA16DW1 / ETSX16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

General Data	
Power supply	3x400V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling



## EN 14511-2

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

## EN 14825

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	3.98
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1188 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	190 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.81	3.63
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5366 kWh	7122 kWh

## Domestic Hot Water (DHW)

### Average Climate

This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DV3 / ETSXB16P30E

### Configure model

Model name	EPRA16DV3 / ETSXB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	4.08
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1158 kWh

## Average Climate



### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	180 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.57	3.62
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5649 kWh	7134 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA16DW1 / ETSXB16P30E

### Configure model

Model name	EPRA16DW1 / ETSXB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	2.93 kW
Cooling capacity	7.88
EER	2.69

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	7.9 kW
SEER	3.98
P <sub>dc</sub> T <sub>j</sub> = 35°C	7.88 kW
EER T <sub>j</sub> = 35°C	2.69
P <sub>dc</sub> T <sub>j</sub> = 30°C	5.92 kW
EER T <sub>j</sub> = 30°C	3.69
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.09 kW
EER T <sub>j</sub> = 25°C	4.63
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.13 kW
EER T <sub>j</sub> = 20°C	5.61
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1188 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	190 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.81	3.63
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.00	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5366 kWh	7122 kWh

## Domestic Hot Water (DHW)

### Average Climate



This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DV3 / ETSH16P30E

Configure model	
Model name	EPRA18DV3 / ETSH16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.17
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1266 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	177 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.51	3.58
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5726 kWh	7211 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DW1 / ETSH16P30E

### Configure model

Model name	EPRA18DW1 / ETSH16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling



**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.07
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1296 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	186 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.71	3.57
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5479 kWh	7236 kWh

## Domestic Hot Water (DHW)

### Average Climate

This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DV3 / ETSHB16P30E

### Configure model

Model name	EPRA18DV3 / ETSHB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.17
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1266 kWh

## Average Climate



### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	177 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.51	3.58
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5726 kWh	7211 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DW1 / ETSHB16P30E

### Configure model

Model name	EPRA18DW1 / ETSHB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.07
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1296 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	186 %	140 %
Prated	12.5 kW	12.5 kW
SCOP	4.71	3.57
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5479 kWh	7236 kWh

## Domestic Hot Water (DHW)

### Average Climate



This information was generated by the HP KEYMARK database on 23 Jun 2022

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DV3 / ETSX16P30E

Configure model	
Model name	EPRA18DV3 / ETSX16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

General Data	
Power supply	1x230V 50Hz

### Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

### Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.17
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1266 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	180 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.57	3.62
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5649 kWh	7134 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DW1 / ETSX16P30E

### Configure model

Model name	EPRA18DW1 / ETSX16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling



**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.07
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1296 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	190 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.81	3.63
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5366 kWh	7122 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DV3 / ETSXB16P30E

### Configure model

Model name	EPRA18DV3 / ETSXB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	1x230V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.41 kW
COP	5.00	3.01

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.17
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.99
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.98
P <sub>off</sub>	21 W
PTO	41 W
PSB	21 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1266 kWh

## Average Climate



### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	180 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.57	3.62
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.1 kW	11.2 kW
COP Tj = -7°C	3.12	2.47
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.7 kW	6.9 kW
COP Tj = +2°C	4.44	3.56
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	5.7 kW	6.9 kW
COP Tj = +7°C	5.84	4.44
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	6.0 kW	6.2 kW
COP Tj = 12°C	7.40	5.72
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	11.1 kW	12.2 kW
COP Tj = Tbiv	3.12	2.19
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.1 kW	12.2 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.76	2.19
WTOL	35 °C	55 °C
Poff	21 W	21 W
PTO	41 W	41 W
PSB	21 W	21 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.4 kW	0.0 kW
Annual energy consumption Qhe	5649 kWh	7134 kWh

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.86
Heating up time	1:25 h:min
Standby power input	57.4 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l

## Model: EPRA18DW1 / ETSXB16P30E

### Configure model

Model name	EPRA18DW1 / ETSXB16P30E
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C

### General Data

Power supply	3x400V 50Hz
--------------	-------------

## Heating

### EN 14511-2

	Low temperature	Medium temperature
Heat output	9.00 kW	7.24 kW
El input	1.80 kW	2.47 kW
COP	5.00	2.93

### EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

## Cooling

**EN 14511-2**

	<b>+7°C/+12°C</b>
El input	3.31 kW
Cooling capacity	8.86
EER	2.68

**EN 14825**

This information was generated by the HP KEYMARK database on 23 Jun 2022

	<b>+7°C/+12°C</b>
P <sub>designc</sub>	8.8 kW
SEER	4.07
P <sub>dc</sub> T <sub>j</sub> = 35°C	8.86 kW
EER T <sub>j</sub> = 35°C	2.68
P <sub>dc</sub> T <sub>j</sub> = 30°C	6.61 kW
EER T <sub>j</sub> = 30°C	3.72
C <sub>dc</sub>	0.98
P <sub>dc</sub> T <sub>j</sub> = 25°C	5.12 kW
EER T <sub>j</sub> = 25°C	4.68
C <sub>dc</sub>	0.97
P <sub>dc</sub> T <sub>j</sub> = 20°C	5.31 kW
EER T <sub>j</sub> = 20°C	5.81
C <sub>dc</sub>	0.97
P <sub>off</sub>	31 W
PTO	33 W
PSB	42 W
PCK	0 W
Annual energy consumption Q <sub>ce</sub>	1296 kWh

## Average Climate

### EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45.6 dB(A)	45.6 dB(A)
Sound power level outdoor	54.0 dB(A)	54.0 dB(A)

### EN 14825

	Low temperature	Medium temperature
$\eta_s$	190 %	142 %
Prated	12.5 kW	12.5 kW
SCOP	4.81	3.63
Tbiv	-7 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	10.7 kW	11.1 kW
COP Tj = -7°C	2.97	2.43
Cdh Tj = -7 °C	1.0	1.0
Pdh Tj = +2°C	6.9 kW	6.7 kW
COP Tj = +2°C	4.94	3.52
Cdh Tj = +2 °C	1.0	1.0
Pdh Tj = +7°C	6.2 kW	6.5 kW
COP Tj = +7°C	5.95	4.54
Cdh Tj = +7 °C	1.0	1.0

This information was generated by the HP KEYMARK database on 23 Jun 2022

Pdh Tj = 12°C	5.6 kW	5.2 kW
COP Tj = 12°C	7.07	5.97
Cdh Tj = +12 °C	1.0	1.0
Pdh Tj = Tbiv	10.7 kW	12.5 kW
COP Tj = Tbiv	2.97	2.12
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.1 kW	12.5 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.88	2.12
WTOL	35 °C	55 °C
Poff	31 W	31 W
PTO	33 W	33 W
PSB	42 W	42 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.4 kW	0.0 kW
Annual energy consumption Qhe	5366 kWh	7122 kWh

## Domestic Hot Water (DHW)

### Average Climate



<b>EN 16147</b>	
Declared load profile	L
Efficiency $\eta_{DHW}$	124 %
COP	2.85
Heating up time	1:25 h:min
Standby power input	57.7 W
Reference hot water temperature	47.0 °C
Mixed water at 40°C	193.0 l