

This information was generated by the HP KEYMARK database on 27 Jun 2022

[Login](#)

Summary of	DC Inverter Air to Water Heat Pump Unit-R32-XC 12	Reg. No.	041-K027-03
Certificate Holder			
Name	Zhongshan Amitime Electric Co., Ltd		
Address	5th Yandong Rd	Zip	
City	Zhongshan City - Guangdong	Country	China
Certification Body	BRE Global Limited		
Subtype title	DC Inverter Air to Water Heat Pump Unit-R32-XC 12		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	1.3 kg		
Certification Date	27.06.2022		
Testing basis	Heat Pump Keymark Scheme Rules Rev 09		

Model: PAVH-12V1FXC

Configure model

Model name	PAVH-12V1FXC
Application	Heating (medium temp)
Units	Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data

Power supply	1x230V 50Hz
--------------	-------------

Heating

EN 14511-2

	Low temperature	Medium temperature
Heat output	10.69 kW	10.43 kW
El input	2.74 kW	4.10 kW
COP	3.91	2.54

EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 27 Jun 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level outdoor	68 dB(A)	68 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	179 %	132 %
Prated	8.75 kW	7.94 kW
SCOP	4.56	3.38
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7.74 kW	7.02 kW
COP Tj = -7°C	2.98	1.94
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	5.24 kW	4.58 kW
COP Tj = +2°C	4.26	3.28
Cdh Tj = +2 °C	0.990	0.990
Pdh Tj = +7°C	4.47 kW	4.24 kW
COP Tj = +7°C	6.19	4.62
Cdh Tj = +7 °C	0.990	0.990
Pdh Tj = 12°C	5.37 kW	5.11 kW

This information was generated by the HP KEYMARK database on 27 Jun 2022

COP Tj = 12°C	8.77	6.89
Cdh Tj = +12 °C	0.990	0.990
Pdh Tj = Tbiv	7.74 kW	7.02 kW
COP Tj = Tbiv	2.98	1.94
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.04 kW	6.19 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.71	1.60
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	57 °C	57 °C
Poff	16 W	16 W
PTO	16 W	16 W
PSB	16 W	16 W
PCK	29 W	29 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.71 kW	1.75 kW
Annual energy consumption Qhe	3966 kWh	4844 kWh