

Page 1 of 4

This information was generated by the HP KEYMARK database on 18 Mar 2022

Login

Summary of	Buderus Logatherm WPS 13-1	Reg. No.	011-1W0183
Certificate Holder			
Name	Bosch Thermotechnik GmbH (Buderus)		
Address	Sophienstraße 30-32	Zip	35576
City	Wetzlar	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Buderus Logatherm WPS 13-1		
Heat Pump Type	Brine/Water		
Refrigerant	R410A		
Mass of Refrigerant	2.65 kg		

This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: Buderus Logatherm WPS 13-1

Configure model			
Model name	Buderus Logatherm WPS 13-1		
Application	Heating (medium temp)		
Units	Indoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	12.82 kW	11.95 kW	
El input	2.82 kW	4.11 kW	
СОР	4.54	2.91	

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	48 dB(A)	48 dB(A)	

EN 14825		
	Low temperature	Medium temperature
η_{s}	187 %	133 %
Prated	14.00 kW	13.00 kW
SCOP	4.88	3.53
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	12.60 kW	11.60 kW
COP Tj = -7°C	4.67	2.98
Pdh Tj = +2°C	12.70 kW	12.00 kW
COP Tj = +2°C	4.88	3.45
Pdh Tj = +7°C	12.80 kW	12.20 kW
COP Tj = +7°C	5.08	3.89
Pdh Tj = 12°C	12.90 kW	12.40 kW
COP Tj = 12°C	5.27	4.32
Pdh Tj = Tbiv	12.60 kW	11.60 kW
COP Tj = Tbiv	4.67	2.98

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.50 kW	11.40 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.56	2.76
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.00	1.00
WTOL	62 °C	62 °C
Poff	6 W	6 W
РТО	6 W	6 W
PSB	6 W	6 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.70 kW	1.70 kW
Annual energy consumption Qhe	6012 kWh	7703 kWh