

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	Bosch Compress 7000 LW 22	Reg. No.	011-1W0152
Certificate Holder			
Name	Bosch Thermotechnik GmbH		
Address	Junkersstraße 20 - 24	Zip	73249
City	Wernau	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Name of testing laboratory	RISE Research Institutes of Sweden	RISE Research Institutes of Sweden AB	
Subtype title	Bosch Compress 7000 LW 22		
Heat Pump Type	Brine/Water		
Refrigerant	R410a		
Mass Of Refrigerant	4.5 kg		



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: Bosch Compress 7000 LW 22

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	22.90 kW	23.27 kW	
El input	5.01 kW	7.73 kW	
СОР	4.57	3.01	
Indoor water flow rate	3.94 m³/h	2.51 m³/h	

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed

Average Climate



This information was generated by the HP KEYMARK database on 17 Dec 2020

	EN 12102-1		
	Low temperature	Medium temperature	
Sound power level indoor	57 dB(A)	57 dB(A)	

EN 14825		
	Low temperature	Medium temperature
η_{s}	207 %	160 %
Prated	21.00 kW	21.00 kW
SCOP	5.38	4.19
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	18.58 kW	18.58 kW
COP Tj = -7°C	4.80	3.31
Pdh Tj = +2°C	11.77 kW	11.78 kW
COP Tj = +2°C	5.54	4.31
Pdh Tj = +7°C	11.76 kW	11.77 kW
COP Tj = +7°C	5.65	4.61
Pdh Tj = 12°C	11.74 kW	11.76 kW
COP Tj = 12°C	5.67	4.88
Pdh Tj = Tbiv	22.90 kW	23.27 kW
COP Tj = Tbiv	4.57	3.01

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}4 of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$

Pdh Tj = TOL	22.90 kW	23.27 kW
COP Tj = TOL	4.57	3.01
Cdh	1.00	1.00
WTOL	68 °C	68 °C
Poff	25 W	25 W
РТО	25 W	25 W
PSB	25 W	25 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electric	Electric
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	8072 kWh	10349 kWh