

Page 1 of 4

This information was generated by the HP KEYMARK database on 18 Mar 2022

	_	_		
- 1	_	$\boldsymbol{\alpha}$	n	

Summary of	Bosch Compress 6000 13 LW	Reg. No.	011-1W0175	
Certificate Holder				
Name	Bosch Thermotechnik GmbH			
Address	Junkersstraße 20 - 24	Zip	73249	
City	Wernau	Country	Germany	
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH			
Subtype title	Bosch Compress 6000 13 LW			
Heat Pump Type	Brine/Water			
Refrigerant	R410A			
Mass of Refrigerant	2.65 kg			



This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: Bosch Compress 6000 13 LW

Configure model			
Model name	Bosch Compress 6000 13 LW		
Application	Heating (medium temp)		
Units	Indoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	12.91 kW	11.83 kW	
El input	2.84 kW	3.97 kW	
СОР	4.55	2.98	

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	48 dB(A)	48 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	187 %	133 %	
Prated	14.00 kW	13.00 kW	
SCOP	4.88	3.53	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	12.60 kW	11.60 kW	
COP Tj = -7°C	4.67	2.98	
Pdh Tj = +2°C	12.70 kW	12.00 kW	
COP Tj = +2°C	4.88	3.45	
Pdh Tj = +7°C	12.80 kW	12.20 kW	
COP Tj = +7°C	5.08	3.89	
Pdh Tj = 12°C	12.90 kW	12.40 kW	
COP Tj = 12°C	5.27	4.32	
Pdh Tj = Tbiv	12.60 kW	11.60 kW	
COP Tj = Tbiv	4.67	2.98	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.50 kW	11.40 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.56	2.76
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.00	1.00
WTOL	62 °C	62 °C
Poff	6 W	6 W
РТО	6 W	6 W
PSB	6 W	6 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.70 kW	1.70 kW
Annual energy consumption Qhe	6012 kWh	7703 kWh