

Page 1 of 5 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	AQUASET PHIAM06	Reg. No.	ICIM-PDC-000016	
Certificate Holder				
Name	NIBE ENERGY SYSTEMS FRANC	NIBE ENERGY SYSTEMS FRANCE		
Address	Route Departementale 28	Zip	01600	
City	Reyrieux	Country	France	
Certification Body	ICIM S.p.A.	ICIM S.p.A.		
Name of testing laboratory	CEIS			
Subtype title	AQUASET PHIAM06			
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R410a			
Mass Of Refrigerant	1.3 kg			
Certification Date	22.11.2018			



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: AQUASET PHIAM06

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2	
	Medium temperature
Heat output	4.00 kW
El input	1.96 kW
СОР	2.04
Indoor water flow rate	0.45 m³/h

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

Average Climate



This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1	
	Medium temperature
Sound power level outdoor	65 dB(A)

EN 14825	
	Medium temperature
η_{s}	111 %
Prated	3.51 kW
SCOP	2.85
Tbiv	-7 °C
TOL	-10 °C
Pdh Tj = -7°C	3.10 kW
COP Tj = -7°C	1.70
Pdh Tj = +2°C	1.95 kW
COP Tj = +2°C	2.84
Pdh Tj = +7°C	1.43 kW
COP Tj = +7°C	3.84
Pdh Tj = 12°C	1.29 kW
COP Tj = 12°C	5.24
Pdh Tj = Tbiv	3.10 kW
COP Tj = Tbiv	1.70
	I I

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com





 $$\operatorname{\textit{Page}}4 of 5$$ This information was generated by the HP KEYMARK database on 17 Dec 2020

Pdh Tj = TOL	2.19 kW
COP Tj = TOL	1.13
Cdh	0.90
WTOL	55 °C
Poff	5 W
PTO	8 W
PSB	5 W
PCK	35 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	1.32 kW
Annual energy consumption Qhe	2546 kWh

Domestic Hot Water (DHW)

Average Climate





 $$\operatorname{\textit{Page}}\xspace\:5\:\:\text{of}\:5\:$ This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 16147		
Declared load profile	XL	
Efficiency ηDHW	86 %	
СОР	2.13	
Heating up time	4:04 h:min	
Standby power input	50.0 W	
Reference hot water temperature	46.7 °C	
Mixed water at 40°C	364 I	