

Page 1 of 4

## This information was generated by the HP KEYMARK database on 18 Mar 2022

Summary of	Bosch Compress 6000 8 LW	Reg. No.	011-1W0173	
Certificate Holder				
Name	Bosch Thermotechnik GmbH	Bosch Thermotechnik GmbH		
Address	Junkersstraße 20 - 24	Zip	73249	
City	Wernau	Country	Germany	
Certification Body	DIN CERTCO Gesellschaft für Konfo	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Bosch Compress 6000 8 LW	Bosch Compress 6000 8 LW		
Heat Pump Type	Brine/Water			
Refrigerant	R410A	R410A		
Mass of Refrigerant	1.95 kg			

This information was generated by the HP KEYMARK database on 18 Mar 2022

## **Model: Bosch Compress 6000 8 LW**

Configure model			
Model name	Bosch Compress 6000 8 LW		
Application	Heating (medium temp)		
Units	Indoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

## Heating

EN 14511-2			
Low temperature Medium temperature			
Heat output	7.46 kW	6.78 kW	
El input	1.64 kW	2.35 kW	
СОР	4.54	2.89	

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	

## Average Climate



This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	47 dB(A)	47 dB(A)

	Low temperature	Medium temperature
	Low temperature	Frediam temperature
N <sub>s</sub>	186 %	131 %
Prated	9.00 kW	8.00 kW
SCOP	4.85	3.48
ГЬіν	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7.50 kW	6.80 kW
COP Tj = -7°C	4.66	2.92
Pdh Tj = +2°C	7.60 kW	7.00 kW
COP Tj = +2°C	4.87	3.43
Pdh Tj = +7°C	7.70 kW	7.20 kW
COP Tj = +7°C	5.07	3.86
Pdh Tj = 12°C	7.80 kW	7.40 kW
COP Tj = 12°C	5.26	4.29
Pdh Tj = Tbiv	7.50 kW	6.80 kW
COP Tj = Tbiv	4.66	2.92

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.50 kW	6.70 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.55	2.68
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.00	1.00
WTOL	62 °C	62 °C
Poff	6 W	6 W
РТО	6 W	6 W
PSB	6 W	6 W
PCK	o w	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.00 kW	1.00 kW
Annual energy consumption Qhe	3619 kWh	4540 kWh