

This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	LWC 60	Reg. No.	041-K001-27
Certificate Holder			
Name	ait-deutschland GmbH		
Address	Industriestr. 3	Zip	95359
City	Kasendorf	Country	Germany
Certification Body	BRE Energy & Communications Division		
Name of testing laboratory	WPZ		
Subtype title	LWC 60		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R407c		
Mass Of Refrigerant	2.95 kg		
Certification Date	06.09.2019		

Model: LWC 60

General Data

Power supply	3x400V 50Hz
--------------	-------------

Heating

EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Starting and operating test	passed

EN 14511-2

	Low temperature	Medium temperature
Heat output	7.00 kW	6.30 kW
El input	1.67 kW	2.74 kW
COP	4.20	2.30
Indoor water flow rate	1.30 m ³ /h	1.30 m ³ /h

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	55 dB(A)	55 dB(A)

This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 14825

	Low temperature	Medium temperature
η_s	148 %	120 %
Prated	6.29 kW	5.90 kW
SCOP	3.78	3.08
Tbiv	-5 °C	-5 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	4.74 kW	4.42 kW
COP Tj = -7°C	2.91	2.02
Cdh	1.00	1.00
Pdh Tj = +2°C	6.23 kW	6.02 kW
COP Tj = +2°C	3.79	3.07
Cdh	0.99	1.00
Pdh Tj = +7°C	7.11 kW	6.99 kW
COP Tj = +7°C	4.78	4.16
Cdh	0.99	0.99
Pdh Tj = 12°C	8.09 kW	8.08 kW
COP Tj = 12°C	5.09	4.96
Cdh	0.99	0.99
Pdh Tj = Tbiv	5.08 kW	4.77 kW
COP Tj = Tbiv	3.14	2.23

This information was generated by the HP KEYMARK database on 17 Dec 2020

Pdh Tj = TOL	4.27 kW	3.92 kW
COP Tj = TOL	2.63	1.76
WTOL	60 °C	60 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	2.02 kW	1.98 kW
Annual energy consumption Qhe	3435 kWh	3957 kWh

Warmer Climate

EN 14825		
	Low temperature	Medium temperature
η_s	180 %	146 %
Prated	7.63 kW	7.18 kW
SCOP	4.57	3.72
Tbiv	4 °C	4 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	6.17 kW	5.74 kW
COP Tj = +2°C	3.57	2.44

This information was generated by the HP KEYMARK database on 17 Dec 2020

Cdh	1.00	1.00
Pdh Tj = +7°C	7.06 kW	6.77 kW
COP Tj = +7°C	4.59	3.37
Cdh	0.99	1.00
Pdh Tj = 12°C	8.07 kW	8.00 kW
COP Tj = 12°C	5.10	4.64
Cdh	0.99	0.99
Pdh Tj = Tbiv	6.54 kW	6.15 kW
COP Tj = Tbiv	4.00	2.77
Pdh Tj = TOL	6.17 kW	5.74 kW
COP Tj = TOL	3.57	2.44
WTOL	60 °C	60 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	1.46 kW	1.44 kW
Annual energy consumption Qhe	2229 kWh	2579 kWh

Colder Climate

This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 14825

	Low temperature	Medium temperature
η_s	130 %	106 %
Prated	5.46 kW	5.09 kW
SCOP	3.32	2.73
Tbiv	-12 °C	-12 °C
TOL	-20 °C	-20 °C
Pdh Tj = -7°C	4.79 kW	4.56 kW
COP Tj = -7°C	3.11	2.35
Cdh	0.99	1.00
Pdh Tj = +2°C	6.28 kW	6.13 kW
COP Tj = +2°C	3.93	3.38
Cdh	0.99	0.99
Pdh Tj = +7°C	7.14 kW	7.08 kW
COP Tj = +7°C	4.88	4.52
Cdh	0.99	0.99
Pdh Tj = 12°C	8.09 kW	8.12 kW
COP Tj = 12°C	4.88	5.01
Cdh	0.99	0.99
Pdh Tj = Tbiv	4.03 kW	3.75 kW
COP Tj = Tbiv	2.68	1.89

This information was generated by the HP KEYMARK database on 17 Dec 2020

Pdh Tj = TOL	2.78 kW	2.63 kW
COP Tj = TOL	1.86	1.29
WTOL	60 °C	60 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	5.46 kW	5.09 kW
Annual energy consumption Qhe	4060 kWh	4592 kWh
Pdh Tj = -15°C (if TOL<-20°C)	3.56	3.27
COP Tj = -15°C (if TOL<-20°C)	2.37	1.63
Cdh	1.00	1.00