

Page 1 of 4

This information was generated by the HP KEYMARK database on 6 Apr 2022

<u>Login</u>

Summary of	Austria Email LWPM 11	Reg. No.	012-C700118	
Certificate Holder				
Name	Groupe Atlantic	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000	
City	La Roche Sur Yon	Country	France	
Certification Body	RISE CERT	RISE CERT		
Subtype title	Austria Email LWPM 11	Austria Email LWPM 11		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R452B	R452B		
Mass of Refrigerant	2.85 kg			
Certification Date	12.11.2021			
Testing basis	EN 14511:2018, EN 14825:2018, EN 12102:2017			



This information was generated by the HP KEYMARK database on 6 Apr 2022

Model: Austria Email LWPM 11

Configure model			
Model name	Austria Email LWPM 11		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	5.81 kW	9.28 kW	
El input	1.29 kW	3.29 kW	
СОР	4.52	2.82	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

Average Climate



This information was generated by the HP KEYMARK database on 6 Apr 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	54 dB(A)	54 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	175 %	130 %	
Prated	9.80 kW	9.60 kW	
SCOP	4.45	3.33	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	8.70 kW	8.50 kW	
COP Tj = -7°C	3.07	2.22	
Cdh Tj = -7 °C	0.970	0.980	
Pdh Tj = +2°C	5.30 kW	5.20 kW	
COP Tj = +2°C	4.58	3.35	
Cdh Tj = +2 °C	0.970	0.980	
Pdh Tj = +7°C	6.00 kW	5.90 kW	
COP Tj = +7°C	5.42	4.19	
Cdh Tj = +7 °C	0.970	0.980	
Pdh Tj = 12°C	7.00 kW	6.80 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 6 Apr 2022

COP Tj = 12°C	6.55	5.18
Cdh Tj = +12 °C	0.970	0.980
Pdh Tj = Tbiv	8.70 kW	8.50 kW
COP Tj = Tbiv	3.07	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.90 kW	7.70 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.83	2.01
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.970	0.980
WTOL	60 °C	60 °C
Poff	18 W	18 W
РТО	36 W	25 W
PSB	20 W	20 W
PCK	o w	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.90 kW	1.90 kW
Annual energy consumption Qhe	4552 kWh	5964 kWh