

Page 1 of 4

This information was generated by the HP KEYMARK database on 23 Jun 2022

Login

Summary of	LA 35TBS	Reg. No.	40054223	
Certificate H	Certificate Holder			
Name	Glen Dimplex Deutschland GmbH			
Address	Am Goldenen Feld 18	Zip	D-95326	
City	Kulmbach	Country	Germany	
Certification Body	VDE Prüf- und Zertifizierungsinstitut GmbH			
Subtype title	LA 35TBS			
Heat Pump Type	Outdoor Air/Water			
Refrigerant	R407c			
Mass of Refrigerant	5.6 kg			
Certification Date	21.10.2021			
Testing basis	DIN EN 14511-1:2019-07; EN 14511-1:2018 , DIN EN 14511-2:2019-07; EN 14511-2:2018, DIN EN 14511-3:2019-07; EN 14511-3:2018, DIN EN 14511-4:2019-07; EN 14511-4:2018, DIN EN 14825:2019-07; EN 14825:2018, DIN EN 12102-1:2018-02; EN 12102-1:2017			



Model: LA 35TBS

Configure model			
Model name	LA 35TBS		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply 3x400V 50Hz		

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	17.60 kW	17.40 kW	
El input	4.07 kW	5.58 kW	
СОР	4.33	3.11	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

Average Climate



 $$\operatorname{\textit{Page}}\ 3$$ of 4 This information was generated by the HP KEYMARK database on 23 Jun 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	61 dB(A)	61 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	152 %	125 %	
Prated	20.70 kW	20.70 kW	
SCOP	3.87	3.21	
Tbiv	-10 °C	-10 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	21.80 kW	22.20 kW	
$COPTj = -7^{\circ}C$	3.02	2.36	
Cdh Tj = -7 °C	1.000	1.000	
Pdh Tj = +2°C	14.30 kW	14.10 kW	
COP Tj = +2°C	3.88	3.22	
Cdh Tj = +2 °C	0.990	1.000	
Pdh Tj = +7°C	18.00 kW	17.60 kW	
$COP Tj = +7^{\circ}C$	4.79	3.95	
Cdh Tj = +7 °C	0.990	1.000	
Pdh Tj = 12°C	21.90 kW	21.30 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 23 Jun 2022

COP Tj = 12°C	5.72	4.93
Cdh Tj = +12 °C	0.990	1.000
Pdh Tj = Tbiv	20.50 kW	20.60 kW
COP Tj = Tbiv	2.90	2.17
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	20.50 kW	20.60 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.90	2.17
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	60 °C	60 °C
Poff	20 W	20 W
РТО	20 W	20 W
PSB	20 W	20 W
PCK	88 W	88 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.20 kW	0.10 kW
Annual energy consumption Qhe	11198 kWh	13342 kWh