

This information was generated by the HP KEYMARK database on 15 Mar 2021

Summary of	WPE-I 44 H 400 Premium	Reg. No.	011-1W0333
Certificate Holder			
Name	STIEBEL ELTRON GmbH & Co KG		
Address	Dr. Stiebel Straße 33	Zip	37603
City	Holzminden	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	WPE-I 44 H 400 Premium		
Heat Pump Type	Brine/Water		
Refrigerant	R410a		
Mass Of Refrigerant	4.4 kg		
Certification Date	05.10.2020		
Testing basis	HP KEYMARK certification scheme rules rev. 7		

Model: WPE-I 44 H 400 Premium

General Data

Power supply	3x400V 50Hz
--------------	-------------

Heating

EN 14511-2

	Low temperature	Medium temperature
Heat output	26.71 kW	22.39 kW
El input	5.81 kW	7.52 kW
COP	4.60	2.98

EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	failed
Starting and operating test	passed

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	48 dB(A)	50 dB(A)

This information was generated by the HP KEYMARK database on 15 Mar 2021

EN 14825

	Low temperature	Medium temperature
η_s	218 %	168 %
Prated	38.06 kW	35.62 kW
SCOP	5.65	4.39
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	33.67 kW	31.51 kW
COP Tj = -7°C	4.56	3.21
Cdh	0.90	0.90
Pdh Tj = +2°C	20.49 kW	19.18 kW
COP Tj = +2°C	5.68	4.39
Cdh	0.90	0.90
Pdh Tj = +7°C	13.18 kW	12.33 kW
COP Tj = +7°C	6.28	5.16
Cdh	0.90	0.90
Pdh Tj = 12°C	12.70 kW	12.57 kW
COP Tj = 12°C	6.31	5.34
Cdh	0.90	0.90
Pdh Tj = Tbiv	38.06 kW	35.62 kW
COP Tj = Tbiv	4.29	2.95

This information was generated by the HP KEYMARK database on 15 Mar 2021

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	38.06 kW	35.62 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.29	2.95
WTOL	65 °C	65 °C
Poff	7 W	7 W
PTO	7 W	7 W
PSB	7 W	7 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	No	No
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	13917 kWh	16768 kWh

Warmer Climate

EN 14825		
	Low temperature	Medium temperature
η_s	220 %	167 %
Prated	38.06 kW	35.62 kW
SCOP	5.70	4.38
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	38.06 kW	35.62 kW
COP Tj = +2°C	4.29	2.95

This information was generated by the HP KEYMARK database on 15 Mar 2021

Cdh	0.90	0.90
Pdh Tj = +7°C	24.47 kW	22.90 kW
COP Tj = +7°C	5.35	3.89
Cdh	0.90	0.90
Pdh Tj = 12°C	12.71 kW	12.48 kW
COP Tj = 12°C	6.31	5.17
Cdh	0.90	0.90
Pdh Tj = Tbiv	38.06 kW	35.62 kW
COP Tj = Tbiv	4.29	2.95
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	38.06 kW	35.62 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.29	2.95
WTOL	65 °C	65 °C
Poff	7 W	7 W
PTO	7 W	7 W
PSB	7 W	7 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	No	No
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	8920 kWh	10862 kWh

This information was generated by the HP KEYMARK database on 15 Mar 2021

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	48 dB(A)	50 dB(A)

Colder Climate

EN 14825		
	Low temperature	Medium temperature
η_s	226 %	174 %
Prated	38.06 kW	35.62 kW
SCOP	5.86	4.55
Tbiv	-22 °C	-22 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	23.04 kW	21.56 kW
COP Tj = -7°C	5.57	4.12
Cdh	0.90	0.90
Pdh Tj = +2°C	14.02 kW	13.12 kW
COP Tj = +2°C	6.27	5.02
Cdh	0.90	0.90
Pdh Tj = +7°C	12.71 kW	12.56 kW
COP Tj = +7°C	6.35	5.32
Cdh	0.90	0.90

This information was generated by the HP KEYMARK database on 15 Mar 2021

Pdh Tj = 12°C	12.70 kW	12.65 kW
COP Tj = 12°C	6.19	5.49
Cdh	0.90	0.90
Pdh Tj = Tbiv	38.06 kW	35.62 kW
COP Tj = Tbiv	4.29	2.95
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	38.06 kW	35.62 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.29	2.95
WTOL	65 °C	65 °C
Poff	7 W	7 W
PTO	7 W	7 W
PSB	7 W	7 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	No	No
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	16014 kWh	19290 kWh
Pdh Tj = -15°C (if TOL<-20°C)	38.06	35.62
COP Tj = -15°C (if TOL<-20°C)	4.29	2.95
Cdh	0.90	0.90

This information was generated by the HP KEYMARK database on 15 Mar 2021

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	48 dB(A)	50 dB(A)