This information was generated by the HP KEYMARK database on 18 Mar 2022

Login

| Summary of | AEROTOP S05.2 | Reg. No. | 011-1W0390 |
|---|---|---|---|
| Certificate Holder | | | |
| Name | ELCO GmbH | | |
| Address | Hohenzollernstrasse 31 | Zip | 72379 |
| City | Hechingen | Country | Germany |
| Certification Body | DIN CERTCO Gesellschaft für Konformitätsbewertung mbH | | |
| Subtype title | AEROTOP S05.2 | | |
| Heat Pump Type | Outdoor Air/Water | | |
| Refrigerant | R410A | | |
| Mass of Refrigerant | 4 kg | | |
| Certification Date | 28.07.2020 | | |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

# Model: AEROTOP S05.2

| Configure model | |
|---|---|
| Model name | AEROTOP S05.2 |
| Application | Heating (medium temp) |
| Units | Indoor |
| Climate Zone | Colder Climate + Warmer Climate |
| Reversibility | Yes |
| Cooling mode application (optional) | n/a |

| General Data | |
|---|---|
| Power supply | 3x400V 50Hz |

## Heating

| EN 14511-4 | |
|---|---|
| | |
| Shutting off the heat transfer medium flow | passed |
| Complete power supply failure | passed |
| Defrost test | passed |
| Starting and operating test | passed |

| EN 14511-2 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Heat output | 4.91 kW | 4.19 kW |
| El input | 1.14 kW | 1.55 kW |
| COP | 4.31 | 2.77 |

## Average Climate



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

## EN 14825

| | Low temperature | Medium temperature |
|---|---|---|
| $\eta_s$ | 180 % | 129 % |
| Prated | 5.97 kW | 4.75 kW |
| SCOP | 4.58 | 3.29 |
| Tbiv | -7 °C | -7 °C |
| TOL | -20 °C | -20 °C |
| Pdh Tj = -7°C | 5.28 kW | 4.20 kW |
| COP Tj = -7°C | 3.57 | 2.21 |
| Cdh Tj = -7 °C | 0.98 | 0.98 |
| Pdh Tj = +2°C | 3.11 kW | 2.67 kW |
| COP Tj = +2°C | 4.64 | 3.46 |
| Cdh Tj = +2 °C | 0.96 | 0.96 |
| Pdh Tj = +7°C | 2.60 kW | 2.51 kW |
| COP Tj = +7°C | 5.65 | 4.18 |
| Cdh Tj = +7 °C | 0.94 | 0.94 |
| Pdh Tj = 12°C | 3.07 kW | 3.00 kW |
| COP Tj = 12°C | 3.57 | 5.66 |
| Cdh Tj = +12 °C | 0.93 | 0.93 |
| Pdh Tj = Tbiv | 5.28 kW | 4.20 kW |
| COP Tj = Tbiv | 3.57 | 2.21 |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 5.84 kW | 5.44 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 2.95 | 1.96 |
| WTOL | 63 °C | 63 °C |
| Poff | 35 W | 35 W |
| PTO | 36 W | 36 W |
| PSB | 15 W | 15 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |
| Supplementary Heater: PSUP | 0.13 kW | 0.00 kW |
| Annual energy consumption Qhe | 2691 kWh | 2977 kWh |

| **EN 12102-1** | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Sound power level indoor | 44 dB(A) | 44 dB(A) |

## Warmer Climate

| **EN 14825** | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| $\eta_s$ | 226 % | 163 % |
| Prated | 5.83 kW | 5.75 kW |
| SCOP | 5.74 | 4.14 |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Tbiv | 2 °C | 2 °C |
| TOL | -20 °C | -20 °C |
| Pdh Tj = +2°C | 5.83 kW | 5.75 kW |
| COP Tj = +2°C | 3.20 | 2.86 |
| Cdh Tj = +2 °C | 0.98 | 0.98 |
| Pdh Tj = +7°C | 3.70 kW | 3.74 kW |
| COP Tj = +7°C | 5.61 | 3.70 |
| Cdh Tj = +7 °C | 0.96 | 0.96 |
| Pdh Tj = 12°C | 3.04 kW | 2.97 kW |
| COP Tj = 12°C | 7.24 | 5.21 |
| Cdh Tj = +12 °C | 0.94 | 0.94 |
| Pdh Tj = Tbiv | 5.83 kW | 5.75 kW |
| COP Tj = Tbiv | 3.20 | 2.86 |
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 5.83 kW | 5.75 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 3.20 | 2.86 |
| WTOL | 63 °C | 63 °C |
| Poff | 35 W | 35 W |
| PTO | 36 W | 36 W |
| PSB | 15 W | 15 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Supplementary Heater: PSUP | 0.00 kW | 0.00 kW |
| Annual energy consumption Qhe | 1358 kWh | 1854 kWh |

| EN 12102-1 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Sound power level indoor | 44 dB(A) | 44 dB(A) |

## Colder Climate

| EN 12102-1 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Sound power level indoor | 44 dB(A) | 44 dB(A) |

| EN 14825 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| $\eta_s$ | 156 % | 122 % |
| Prated | 7.00 kW | 5.81 kW |
| SCOP | 3.98 | 3.13 |
| Tbiv | -7 °C | -7 °C |
| TOL | -20 °C | -20 °C |
| Pdh Tj = -7°C | 4.47 kW | 3.71 kW |
| COP Tj = -7°C | 3.92 | 2.56 |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Cdh Tj = -7 °C | 0.98 | 0.98 |
| Pdh Tj = +2°C | 2.64 kW | 2.33 kW |
| COP Tj = +2°C | 5.28 | 4.24 |
| Cdh Tj = +2 °C | 0.96 | 0.96 |
| Pdh Tj = +7°C | 2.63 kW | 2.59 kW |
| COP Tj = +7°C | 6.12 | 4.71 |
| Cdh Tj = +7 °C | 0.94 | 0.94 |
| Pdh Tj = 12°C | 3.07 kW | 3.05 kW |
| COP Tj = 12°C | 7.49 | 6.09 |
| Cdh Tj = +12 °C | 0.93 | 0.93 |
| Pdh Tj = Tbiv | 4.47 kW | 3.71 kW |
| COP Tj = Tbiv | 3.92 | 2.56 |
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 4.32 kW | 4.03 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 2.32 | 1.55 |
| WTOL | 63 °C | 63 °C |
| Poff | 35 W | 35 W |
| PTO | 36 W | 36 W |
| PSB | 15 W | 15 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |
| Supplementary Heater: PSUP | 2.68 kW | 1.78 kW |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Annual energy consumption Qhe | 4575 kWh | 4824 kWh |
| Pdh Tj = -15°C (if TOL<-20°C) | | |
| COP Tj = -15°C (if TOL<-20°C) | | |
| Cdh Tj = -15 °C | | |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

# Model: AEROTOP S05.2_2-parts

| Configure model | |
|---|---|
| Model name | AEROTOP S05.2_2-parts |
| Application | Heating (medium temp) |
| Units | Indoor |
| Climate Zone | Colder Climate + Warmer Climate |
| Reversibility | Yes |
| Cooling mode application (optional) | n/a |

| General Data | |
|---|---|
| Power supply | 3x400V 50Hz |

## Heating

| EN 14511-4 | |
|---|---|
| | |
| Shutting off the heat transfer medium flow | passed |
| Complete power supply failure | passed |
| Defrost test | passed |
| Starting and operating test | passed |

| EN 14511-2 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Heat output | 4.91 kW | 4.19 kW |
| El input | 1.14 kW | 1.55 kW |
| COP | 4.31 | 2.77 |

## Average Climate



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

## EN 14825

| | Low temperature | Medium temperature |
|---|---|---|
| $\eta_s$ | 180 % | 129 % |
| Prated | 5.97 kW | 4.75 kW |
| SCOP | 4.58 | 3.29 |
| Tbiv | -7 °C | -7 °C |
| TOL | -20 °C | -20 °C |
| Pdh Tj = -7°C | 5.28 kW | 4.20 kW |
| COP Tj = -7°C | 3.57 | 2.21 |
| Cdh Tj = -7 °C | 0.98 | 0.98 |
| Pdh Tj = +2°C | 3.11 kW | 2.67 kW |
| COP Tj = +2°C | 4.64 | 3.46 |
| Cdh Tj = +2 °C | 0.96 | 0.96 |
| Pdh Tj = +7°C | 2.60 kW | 2.51 kW |
| COP Tj = +7°C | 5.65 | 4.18 |
| Cdh Tj = +7 °C | 0.94 | 0.94 |
| Pdh Tj = 12°C | 3.07 kW | 3.00 kW |
| COP Tj = 12°C | 3.57 | 5.66 |
| Cdh Tj = +12 °C | 0.93 | 0.93 |
| Pdh Tj = Tbiv | 5.28 kW | 4.20 kW |
| COP Tj = Tbiv | 3.57 | 2.21 |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 5.84 kW | 5.44 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 2.95 | 1.96 |
| WTOL | 63 °C | 63 °C |
| Poff | 35 W | 35 W |
| PTO | 36 W | 36 W |
| PSB | 15 W | 15 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |
| Supplementary Heater: PSUP | 0.13 kW | 0.00 kW |
| Annual energy consumption Qhe | 2691 kWh | 2977 kWh |

| **EN 12102-1** | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Sound power level indoor | 44 dB(A) | 44 dB(A) |

## Warmer Climate

| **EN 14825** | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| $\eta_s$ | 226 % | 163 % |
| Prated | 5.83 kW | 5.75 kW |
| SCOP | 5.74 | 4.14 |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Tbiv | 2 °C | 2 °C |
| TOL | -20 °C | -20 °C |
| Pdh Tj = +2°C | 5.83 kW | 5.75 kW |
| COP Tj = +2°C | 3.20 | 2.86 |
| Cdh Tj = +2 °C | 0.98 | 0.98 |
| Pdh Tj = +7°C | 3.70 kW | 3.74 kW |
| COP Tj = +7°C | 5.61 | 3.70 |
| Cdh Tj = +7 °C | 0.96 | 0.96 |
| Pdh Tj = 12°C | 3.04 kW | 2.97 kW |
| COP Tj = 12°C | 7.24 | 5.21 |
| Cdh Tj = +12 °C | 0.94 | 0.94 |
| Pdh Tj = Tbiv | 5.83 kW | 5.75 kW |
| COP Tj = Tbiv | 3.20 | 2.86 |
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 5.83 kW | 5.75 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 3.20 | 2.86 |
| WTOL | 63 °C | 63 °C |
| Poff | 35 W | 35 W |
| PTO | 36 W | 36 W |
| PSB | 15 W | 15 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Supplementary Heater: PSUP | 0.00 kW | 0.00 kW |
| Annual energy consumption Qhe | 1358 kWh | 1854 kWh |

| EN 12102-1 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Sound power level indoor | 44 dB(A) | 44 dB(A) |

## Colder Climate

| EN 12102-1 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| Sound power level indoor | 44 dB(A) | 44 dB(A) |

| EN 14825 | | |
|---|---|---|
| | **Low temperature** | **Medium temperature** |
| $\eta_s$ | 156 % | 122 % |
| Prated | 7.00 kW | 5.81 kW |
| SCOP | 3.98 | 3.13 |
| Tbiv | -7 °C | -7 °C |
| TOL | -20 °C | -20 °C |
| Pdh Tj = -7°C | 4.47 kW | 3.71 kW |
| COP Tj = -7°C | 3.92 | 2.56 |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Cdh Tj = -7 °C | 0.98 | 0.98 |
| Pdh Tj = +2°C | 2.64 kW | 2.33 kW |
| COP Tj = +2°C | 5.28 | 4.24 |
| Cdh Tj = +2 °C | 0.96 | 0.96 |
| Pdh Tj = +7°C | 2.63 kW | 2.59 kW |
| COP Tj = +7°C | 6.12 | 4.71 |
| Cdh Tj = +7 °C | 0.94 | 0.94 |
| Pdh Tj = 12°C | 3.07 kW | 3.05 kW |
| COP Tj = 12°C | 7.49 | 6.09 |
| Cdh Tj = +12 °C | 0.93 | 0.93 |
| Pdh Tj = Tbiv | 4.47 kW | 3.71 kW |
| COP Tj = Tbiv | 3.92 | 2.56 |
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 4.32 kW | 4.03 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 2.32 | 1.55 |
| WTOL | 63 °C | 63 °C |
| Poff | 35 W | 35 W |
| PTO | 36 W | 36 W |
| PSB | 15 W | 15 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |
| Supplementary Heater: PSUP | 2.68 kW | 1.78 kW |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.

| | | |
|---|---|---|
| Annual energy consumption Qhe | 4575 kWh | 4824 kWh |
| Pdh Tj = -15°C (if TOL<-20°C) | | |
| COP Tj = -15°C (if TOL<-20°C) | | |
| Cdh Tj = -15 °C | | |



Disclaimer: this document is a summary of the certified performance.
The authoritative source of this information is the heat pump certificate as executed by the certification body and the related technical data.