

Page 1 of 4 This information was generated by the HP KEYMARK database on 7 Jul 2022

Login

Summary of	Buderus Logatherm WPS 80.2 HT	Reg. No.	011-1W0167	
Certificate Holder	<u>'</u>	'		
Name	Bosch Thermotechnik GmbH (Buderus)			
Address	Sophienstraße 30-32	Zip	35576	
City	Wetzlar	Country	Germany	
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH			
Subtype title	Buderus Logatherm WPS 80.2 HT	Buderus Logatherm WPS 80.2 HT		
Heat Pump Type	Brine/Water			
Refrigerant	R410A			
Mass of Refrigerant	10.8 kg			

This information was generated by the HP KEYMARK database on 7 Jul 2022

Model: Buderus Logatherm WPS 80.2 HT

Configure model			
Model name Buderus Logatherm WPS 80.2 HT			
Application	Heating (medium temp)		
Units	Indoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

Heating

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow		
Complete power supply failure	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	78.16 kW	81.17 kW	
El input	18.17 kW	26.65 kW	
СОР	4.30	3.05	

Average Climate



This information was generated by the HP KEYMARK database on 7 Jul 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	67 dB(A)	67 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	196 %	157 %	
Prated	78.00 kW	78.00 kW	
SCOP	5.10	4.12	
Tbiv	-10 °C	-10 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	69.00 kW	69.00 kW	
COP Tj = -7°C	4.48	3.31	
Pdh Tj = +2°C	42.02 kW	42.24 kW	
COP Tj = +2°C	5.19	4.20	
Pdh Tj = +7°C	41.93 kW	42.28 kW	
COP Tj = +7°C	5.32	4.47	
Pdh Tj = 12°C	41.86 kW	42.33 kW	
COP Tj = 12°C	5.42	4.73	
Pdh Tj = Tbiv	78.16 kW	81.17 kW	
COP Tj = Tbiv	4.30	3.05	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 7 Jul 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	78.16 kW	81.17 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.30	3.05
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.00	1.00
WTOL	68 °C	68 °C
Poff	25 W	25 W
PTO	25 W	25 W
PSB	25 W	25 W
PCK	0 W	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	31613 kWh	39068 kWh