

Page 1 of 4 This information was generated by the HP KEYMARK database on 7 Jul 2022

Login

Summary of	F2040-8	Reg. No.	012-026
Certificate Holder			
Name	Nibe AB		
Address	Box 14	Zip	S-28521
City	Markaryd	Country	Sweden
Certification Body	RISE CERT		
Subtype title	F2040-8		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410A		
Mass of Refrigerant	2.6 kg		



Model: F2040-8

Configure model			
Model name	F2040-8		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	3.86 kW	3.50 kW	
El input	0.83 kW	1.17 kW	
СОР	4.65	2.99	

Average Climate

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	54 dB(A)	54 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	172 %	127 %	
Prated	8.20 kW	7.00 kW	
SCOP	4.37	3.25	
Tbiv	-8 °C	-9 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	7.40 kW	6.30 kW	
COP Tj = -7°C	2.92	1.94	
Pdh Tj = $+2$ °C	4.50 kW	3.90 kW	
COP Tj = +2°C	4.30	3.11	
Pdh Tj = $+7^{\circ}$ C	2.90 kW	2.60 kW	
$COP Tj = +7^{\circ}C$	5.41	4.42	
Pdh Tj = 12°C	3.50 kW	3.70 kW	
COP Tj = 12°C	6.51	5.93	
Pdh Tj = Tbiv	7.40 kW	6.60 kW	
COP Tj = Tbiv	2.86	1.83	
		·	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 7 Jul 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.80 kW	5.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.67	1.86
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.96	0.97
WTOL	58 °C	58 °C
Poff	2 W	2 W
РТО	15 W	10 W
PSB	15 W	15 W
PCK	20 W	20 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.40 kW	1.10 kW
Annual energy consumption Qhe	3882 kWh	4447 kWh