Login

Summary of	Alféa Excellia HP A.I. 16	Reg. No.	012-SC0755-18
Certificate Holder			
Name	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT		
Subtype title	Alféa Excellia HP A.I. 16		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410A		
Mass of Refrigerant	3.8 kg		

Model: Alféa Excellia HP A.I. 16

Configure model	
Model name	Alféa Excellia HP A.I. 16
Application	Heating (medium temp)
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	16.46 kW	14.86 kW
El input	3.94 kW	5.65 kW
COP	4.18	2.63

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	45 dB(A)	45 dB(A)
Sound power level outdoor	67 dB(A)	67 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	163 %	125 %
Prated	16.00 kW	14.00 kW
SCOP	4.15	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	14.20 kW	12.00 kW
COP Tj = -7°C	2.79	1.98
Pdh Tj = +2°C	8.70 kW	7.30 kW
COP Tj = +2°C	4.17	3.15
Pdh Tj = +7°C	7.00 kW	6.30 kW
COP Tj = +7°C	5.34	4.30
Pdh Tj = 12°C	8.10 kW	7.60 kW
COP Tj = 12°C	6.76	5.99
Pdh Tj = Tbiv	14.20 kW	12.00 kW

COP Tj = Tbiv	2.79	1.98
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	14.10 kW	10.60 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.54	1.75
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.92	0.96
WTOL	65 °C	65 °C
Poff	19 W	19 W
PTO	100 W	46 W
PSB	23 W	23 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.00 kW	3.00 kW
Annual energy consumption Qhe	8014 kWh	8757 kWh

Model: Alféa Excellia HP Duo A.I. 16

Configure model	
Model name	Alféa Excellia HP Duo A.I. 16
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	16.46 kW	14.86 kW
El input	3.94 kW	5.65 kW
COP	4.18	2.63

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	45 dB(A)	45 dB(A)
Sound power level outdoor	67 dB(A)	67 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	163 %	125 %
Prated	16.00 kW	14.00 kW
SCOP	4.15	3.21
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	14.20 kW	12.00 kW
COP Tj = -7°C	2.79	1.98
Pdh Tj = +2°C	8.70 kW	7.30 kW
COP Tj = +2°C	4.17	3.15
Pdh Tj = +7°C	7.00 kW	6.30 kW
COP Tj = +7°C	5.34	4.30
Pdh Tj = 12°C	8.10 kW	7.60 kW
COP Tj = 12°C	6.76	5.99
Pdh Tj = Tbiv	14.20 kW	12.00 kW

COP Tj = Tbiv	2.79	1.98
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	14.10 kW	10.60 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.54	1.75
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.92	0.96
WTOL	65 °C	65 °C
Poff	19 W	19 W
PTO	100 W	46 W
PSB	23 W	23 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.00 kW	3.00 kW
Annual energy consumption Qhe	8014 kWh	8757 kWh

Domestic Hot Water (DHW)

Average Climate

EN 16147

Declared load profile	L
Efficiency ηDHW	109 %
COP	2.56
Heating up time	0:54 h:min
Standby power input	48.0 W
Reference hot water temperature	54.2 °C
Mixed water at 40°C	250 l