

This information was generated by the HP KEYMARK database on 18 Mar 2022

[Login](#)

Summary of	DAIKIN ALTHERMA GEO	Reg. No.	011-1W0067
Certificate Holder			
Name	DAIKIN Europe N.V.		
Address	Zandvoordestraat 300	Zip	B-8400
City	Oostende	Country	Belgium
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	DAIKIN ALTHERMA GEO		
Heat Pump Type	Brine/Water		
Refrigerant	R410A		
Mass of Refrigerant	1.8 kg		
Certification Date	17.02.2017		
Testing basis	HP KEYMARK certification scheme rules V8		

Model: EGSQH10S18A9W

Configure model

Model name	EGSQH10S18A9W
Application	Heating + DHW + low temp
Units	Indoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data

Power supply	3x400V 50Hz
Off-peak product	No

Heating

EN 14511-2

	Low temperature	Medium temperature
Heat output	10.30 kW	8.92 kW
El input	2.38 kW	3.35 kW
COP	4.33	2.66

EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	46 dB(A)	46 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	194 %	139 %
Prated	10.40 kW	8.72 kW
SCOP	5.06	3.68
Tbiv	-9 °C	-9 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	9.12 kW	7.76 kW
COP Tj = -7°C	4.40	2.91
Cdh Tj = -7 °C	1.00	1.00
Pdh Tj = +2°C	5.77 kW	4.73 kW
COP Tj = +2°C	5.22	3.73
Cdh Tj = +2 °C	1.00	1.00
Pdh Tj = +7°C	3.82 kW	3.04 kW
COP Tj = +7°C	5.55	4.18
Cdh Tj = +7 °C	1.00	1.00
Pdh Tj = 12°C	2.71 kW	2.61 kW

This information was generated by the HP KEYMARK database on 18 Mar 2022

COP Tj = 12°C	5.55	4.73
Cdh Tj = +12 °C	0.93	0.94
Pdh Tj = Tbiv	10.20 kW	8.46 kW
COP Tj = Tbiv	4.17	2.87
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	10.10 kW	8.41 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.16	2.80
WTOL	35 °C	55 °C
Poff	20 W	20 W
PTO	37 W	37 W
PSB	20 W	20 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.30 kW	0.31 kW
Annual energy consumption Qhe	4260 kWh	4900 kWh

Domestic Hot Water (DHW)

Average Climate

EN 16147	
Declared load profile	L
Standby power input	42.0 W
Reference hot water temperature	52.0 °C
Mixed water at 40°C	199 l
COP	2.28
Efficiency η_{DHW}	93 %
Heating up time	1:25 h:min