

This information was generated by the HP KEYMARK database on 18 Mar 2022

[Login](#)

Summary of	Acond PRO-N	Reg. No.	037-0075-22
Certificate Holder			
Name	Acond a.s.		
Address	Štěrboholská 1434/102a	Zip	102 00
City	Hostivař, Praha	Country	Czech Republic
Certification Body	SZU - Strojirensky zkusebni ustav (Engineering Test Institute, Public Enterprise)		
Subtype title	Acond PRO-N		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R290		
Mass of Refrigerant	1.35 kg		
Certification Date	17.03.2022		
Testing basis	HP Keymark scheme rules rev. no. 9		

Model: Acond PRO-N

Configure model	
Model name	Acond PRO-N
Application	Heating (medium temp)
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	3.04 kW	3.54 kW
El input	0.62 kW	1.17 kW
COP	4.90	3.03

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	dB(A)	0 dB(A)
Sound power level outdoor	dB(A)	48 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	164 %	135 %
Prated	5.29 kW	5.14 kW
SCOP	4.18	3.45
Tbiv	-10 °C	-10 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	4.68 kW	4.54 kW
COP Tj = -7°C	2.98	2.20
Cdh Tj = -7 °C	0.900	0.900
Pdh Tj = +2°C	2.88 kW	2.77 kW
COP Tj = +2°C	4.18	3.42
Cdh Tj = +2 °C	0.900	0.900
Pdh Tj = +7°C	1.83 kW	1.86 kW
COP Tj = +7°C	5.11	4.46
Cdh Tj = +7 °C	0.900	0.900

This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = 12°C	1.81 kW	1.76 kW
COP Tj = 12°C	5.18	4.86
Cdh Tj = +12 °C	0.954	0.959
Pdh Tj = Tbiv	5.29 kW	5.14 kW
COP Tj = Tbiv	2.21	1.88
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.29 kW	5.14 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.21	1.88
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	70 °C	70 °C
Poff	16 W	16 W
PTO	16 W	16 W
PSB	16 W	16 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	n/a	n/a
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2615 kWh	3078 kWh