

Page 1 of 4

### This information was generated by the HP KEYMARK database on 18 Mar 2022

#### Login

Summary of	CTC CombiAir 6M	Reg. No.	012-C700075	
Certificate Holder	'			
Name	Enertech CTC AB	Enertech CTC AB		
Address	Box 309, Näsvägen	Zip	SE-381 26	
City	Ljungby	Country	Sweden	
Certification Body	RISE CERT	RISE CERT		
Subtype title	CTC CombiAir 6M	CTC CombiAir 6M		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R410A			
Mass of Refrigerant	1.5 kg			
Certification Date	30.10.2020			



This information was generated by the HP KEYMARK database on 18 Mar 2022

# Model: CTC CombiAir 6M

Configure model			
Model name	CTC CombiAir 6M		
Application Heating (medium temp)			
Units	Indoor + Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	1x230V 50Hz	

# Heating

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	2.42 kW	1.57 kW	
El input	0.50 kW	0.76 kW	
СОР	4.85	2.06	

# Average Climate



 $$\operatorname{\textit{Page}}\xspace$  3 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	35 dB(A)	35 dB(A)	
Sound power level outdoor	50 dB(A)	50 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
$\eta_{s}$	188 %	131 %	
Prated	4.80 kW	5.30 kW	
SCOP	4.77	3.35	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	4.30 kW	4.70 kW	
COP Tj = -7°C	2.60	1.88	
Pdh Tj = +2°C	2.60 kW	2.80 kW	
COP Tj = +2°C	4.84	3.26	
Pdh Tj = +7°C	1.70 kW	1.80 kW	
COP Tj = +7°C	6.91	4.72	
Pdh Tj = 12°C	2.70 kW	2.70 kW	
COP Tj = 12°C	7.72	6.47	
Pdh Tj = Tbiv	4.30 kW	4.70 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

COP Tj = Tbiv	2.60	1.88
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	3.20 kW	4.10 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.24	1.77
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.98	0.99
WTOL	58 °C	58 °C
Poff	7 W	7 W
РТО	12 W	12 W
PSB	12 W	12 W
PCK	o w	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.60 kW	1.20 kW
Annual energy consumption Qhe	2089 kWh	3248 kWh