Summary of	Samsung EHS R32 Mono 12kW & 16kW (space heating/ 260L)	Reg. No.	011-1W0447
Certificate Holder			
Name	Samsung Electronics Air Conditioner Europe B.V.		
Address	Evert van de Beekstraat 310	Zip	1118 CX
City	Schiphol	Country	Netherlands
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Samsung EHS R32 Mono 12kW & 16kW (space heating/ 260L)		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass Of Refrigerant	2.2 kg		
Certification Date	26.01.2021		
Testing basis	HP KEYMARK certification scheme rules V7		

Model: AE120RXYDEG/EU & AE260RNWMEG/EU

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	12.00 kW	11.30 kW
El input	2.65 kW	3.73 kW
COP	4.53	3.03
Indoor water flow rate	2.08 m³/h	1.22 m³/h

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	64 dB(A)	64 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	185 %	138 %
Prated	13.00 kW	12.00 kW
SCOP	4.69	3.51
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.50 kW	10.62 kW
COP Tj = -7°C	2.71	2.16
Cdh	0.90	0.90
Pdh Tj = +2°C	7.00 kW	6.46 kW
COP Tj = +2°C	4.48	3.45
Cdh	0.90	0.90
Pdh Tj = +7°C	5.60 kW	4.15 kW
COP Tj = +7°C	6.86	4.57
Cdh	0.90	0.90

Pdh Tj = 12°C	4.80 kW	4.40 kW
COP Tj = 12°C	8.95	6.12
Cdh	0.90	0.90
Pdh Tj = Tbiv	11.50 kW	10.62 kW
COP Tj = Tbiv	2.71	2.16
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.00 kW	12.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.37	1.96
WTOL	65 °C	65 °C
Poff	22 W	22 W
PTO	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	5725 kWh	7051 kWh

Domestic Hot Water (DHW)

Average Climate

EN 16147

Declared load profile	XL
Efficiency ηDHW	117 %
COP	2.70
Heating up time	1:50 h:min
Standby power input	67.0 W
Reference hot water temperature	52.0 °C
Mixed water at 40°C	290 l

Model: AE120RXYDGG/EU & MIM-E03CN

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	12.00 kW	11.30 kW
El input	2.65 kW	3.73 kW
COP	4.53	3.03
Indoor water flow rate	2.08 m³/h	1.22 m³/h

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	64 dB(A)	64 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	185 %	138 %
Prated	13.00 kW	12.00 kW
SCOP	4.69	3.51
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.50 kW	10.62 kW
COP Tj = -7°C	2.71	2.16
Cdh	0.90	0.90
Pdh Tj = +2°C	7.00 kW	6.46 kW
COP Tj = +2°C	4.48	3.45
Cdh	0.90	0.90
Pdh Tj = +7°C	5.60 kW	4.15 kW
COP Tj = +7°C	6.86	4.57
Cdh	0.90	0.90

Pdh Tj = 12°C	4.80 kW	4.40 kW
COP Tj = 12°C	8.95	6.12
Cdh	0.90	0.90
Pdh Tj = Tbiv	11.50 kW	10.62 kW
COP Tj = Tbiv	2.71	2.16
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.00 kW	12.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.37	1.96
WTOL	65 °C	65 °C
Poff	22 W	22 W
PTO	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	5725 kWh	7051 kWh

Model: AE120RXYDGG/EU & AE260RNWMGG/EU

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	12.00 kW	11.30 kW
El input	2.65 kW	3.73 kW
COP	4.53	3.03
Indoor water flow rate	2.08 m³/h	1.22 m³/h

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	64 dB(A)	64 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	185 %	138 %
Prated	13.00 kW	12.00 kW
SCOP	4.69	3.51
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.50 kW	10.62 kW
COP Tj = -7°C	2.71	2.16
Cdh	0.90	0.90
Pdh Tj = +2°C	7.00 kW	6.46 kW
COP Tj = +2°C	4.48	3.45
Cdh	0.90	0.90
Pdh Tj = +7°C	5.60 kW	4.15 kW
COP Tj = +7°C	6.86	4.57
Cdh	0.90	0.90

Pdh Tj = 12°C	4.80 kW	4.40 kW
COP Tj = 12°C	8.95	6.12
Cdh	0.90	0.90
Pdh Tj = Tbiv	11.50 kW	10.62 kW
COP Tj = Tbiv	2.71	2.16
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.00 kW	12.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.37	1.96
WTOL	65 °C	65 °C
Poff	22 W	22 W
PTO	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	5725 kWh	7051 kWh

Domestic Hot Water (DHW)

Average Climate

EN 16147

Declared load profile	XL
Efficiency ηDHW	117 %
COP	2.70
Heating up time	1:50 h:min
Standby power input	67.0 W
Reference hot water temperature	52.0 °C
Mixed water at 40°C	290 l

Model: AE160RXYDEG/EU & AE260RNWMEG/EU

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	16.00 kW	15.00 kW
El input	3.62 kW	5.18 kW
COP	4.42	2.90
Indoor water flow rate	2.77 m³/h	1.63 m³/h

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	66 dB(A)	66 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	176 %	138 %
Prated	16.00 kW	16.00 kW
SCOP	4.48	3.53
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	14.15 kW	14.15 kW
COP Tj = -7°C	2.65	2.06
Cdh	0.90	0.90
Pdh Tj = +2°C	8.62 kW	8.62 kW
COP Tj = +2°C	4.11	3.31
Cdh	0.90	0.90
Pdh Tj = +7°C	5.54 kW	5.54 kW
COP Tj = +7°C	6.86	5.23
Cdh	0.90	0.90

Pdh Tj = 12°C	5.20 kW	4.49 kW
COP Tj = 12°C	8.81	6.35
Cdh	0.90	0.90
Pdh Tj = Tbiv	14.15 kW	14.15 kW
COP Tj = Tbiv	2.65	2.06
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.80 kW	14.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.37	1.82
WTOL	65 °C	65 °C
Poff	22 W	22 W
PTO	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	2.20 kW	2.00 kW
Annual energy consumption Qhe	7385 kWh	9379 kWh

Domestic Hot Water (DHW)

Average Climate

EN 16147

Declared load profile	XL
Efficiency ηDHW	117 %
COP	2.70
Heating up time	1:50 h:min
Standby power input	67.0 W
Reference hot water temperature	52.0 °C
Mixed water at 40°C	290 l

Model: AE160RXYDGG/EU & MIM-E03CN

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	16.00 kW	15.00 kW
El input	3.62 kW	5.18 kW
COP	4.42	2.90
Indoor water flow rate	2.77 m³/h	1.63 m³/h

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	66 dB(A)	66 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	176 %	138 %
Prated	16.00 kW	16.00 kW
SCOP	4.48	3.53
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	14.15 kW	14.15 kW
COP Tj = -7°C	2.65	2.06
Cdh	0.90	0.90
Pdh Tj = +2°C	8.62 kW	8.62 kW
COP Tj = +2°C	4.11	3.31
Cdh	0.90	0.90
Pdh Tj = +7°C	5.54 kW	5.54 kW
COP Tj = +7°C	6.86	5.23
Cdh	0.90	0.90

Pdh Tj = 12°C	5.20 kW	4.49 kW
COP Tj = 12°C	8.81	6.35
Cdh	0.90	0.90
Pdh Tj = Tbiv	14.20 kW	14.15 kW
COP Tj = Tbiv	2.65	2.06
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.80 kW	14.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.37	1.82
WTOL	65 °C	65 °C
Poff	22 W	22 W
PTO	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	2.20 kW	2.00 kW
Annual energy consumption Qhe	7385 kWh	9379 kWh

Model: AE160RXYDGG/EU & AE260RNWMGG/EU

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	16.00 kW	15.00 kW
El input	3.62 kW	5.18 kW
COP	4.42	2.90
Indoor water flow rate	2.77 m³/h	1.63 m³/h

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	66 dB(A)	66 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	176 %	138 %
Prated	16.00 kW	16.00 kW
SCOP	4.48	3.53
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	14.15 kW	14.15 kW
COP Tj = -7°C	2.65	2.06
Cdh	0.90	0.90
Pdh Tj = +2°C	8.62 kW	8.62 kW
COP Tj = +2°C	4.11	3.31
Cdh	0.90	0.90
Pdh Tj = +7°C	5.54 kW	5.54 kW
COP Tj = +7°C	6.86	5.23
Cdh	0.90	0.90

Pdh Tj = 12°C	5.20 kW	4.49 kW
COP Tj = 12°C	8.81	6.35
Cdh	0.90	0.90
Pdh Tj = Tbiv	14.20 kW	14.15 kW
COP Tj = Tbiv	2.65	2.06
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.80 kW	14.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.37	1.82
WTOL	65 °C	65 °C
Poff	22 W	22 W
PTO	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	2.20 kW	2.00 kW
Annual energy consumption Qhe	7385 kWh	9379 kWh

Domestic Hot Water (DHW)

Average Climate

EN 16147

Declared load profile	XL
Efficiency ηDHW	117 %
COP	2.70
Heating up time	1:50 h:min
Standby power input	67.0 W
Reference hot water temperature	52.0 °C
Mixed water at 40°C	290 l