

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	Buderus Logatherm WPS 13-1	Reg. No.	011-1W0183
Certificate Holder			
Name	Bosch Thermotechnik GmbH (Buderus)		
Address	Sophienstraße 30-32	Zip	35576
City	Wetzlar	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Name of testing laboratory	IGE Institut für GebäudeEnergetik		
Subtype title	Buderus Logatherm WPS 13-1		
Heat Pump Type	Brine/Water		
Refrigerant	R410a		
Mass Of Refrigerant	2.65 kg		



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: Buderus Logatherm WPS 13-1

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	12.82 kW	11.95 kW
El input	2.82 kW	4.11 kW
СОР	4.54	2.91
Indoor water flow rate	2.21 m³/h	1.30 m³/h

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	

Average Climate



This information was generated by the HP KEYMARK database on 17 Dec 2020

	EN 12102-1		
	Low temperature	Medium temperature	
Sound power level indoor	48 dB(A)	48 dB(A)	

EN 14825		
	Low temperature	Medium temperature
η_{s}	187 %	133 %
Prated	14.00 kW	13.00 kW
SCOP	4.88	3.53
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	12.60 kW	11.60 kW
COP Tj = -7°C	4.67	2.98
Pdh Tj = +2°C	12.70 kW	12.00 kW
COP Tj = +2°C	4.88	3.45
Pdh Tj = +7°C	12.80 kW	12.20 kW
COP Tj = +7°C	5.08	3.89
Pdh Tj = 12°C	12.90 kW	12.40 kW
COP Tj = 12°C	5.27	4.32
Pdh Tj = Tbiv	12.60 kW	11.60 kW
COP Tj = Tbiv	4.67	2.98

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}4 of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$

Pdh Tj = TOL	12.50 kW	11.40 kW
COP Tj = TOL	4.56	2.76
Cdh	1.00	1.00
WTOL	62 °C	62 °C
Poff	6 W	6 W
PTO	6 W	6 W
PSB	6 W	6 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electric	Electric
Supplementary Heater: PSUP	1.70 kW	1.70 kW
Annual energy consumption Qhe	6012 kWh	7703 kWh