

Page 1 of 4

This information was generated by the HP KEYMARK database on 18 Mar 2022

<u>Login</u>

Summary of	AUREA 5 R32	Reg. No.	012-C700073
Certificate Holder	'	'	
Name	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT		
Subtype title	AUREA 5 R32		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	0.8 kg		
Certification Date	27.05.2020		
Testing basis	HP Keymark Scheme Rules rev 7		



This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: AUREA 5 R32

Configure model			
Model name	AUREA 5 R32		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data			
Power supply 1x230V 50Hz			

Heating

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	5.30 kW	4.90 kW	
El input	1.14 kW	1.73 kW	
СОР	4.62	2.83	

Average Climate



This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	63 dB(A)	63 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	183 %	127 %	
Prated	5.00 kW	5.00 kW	
SCOP	4.64	3.26	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	4.10 kW	4.20 kW	
COP Tj = -7°C	2.86	1.94	
Cdh Tj = -7 °C	0.90	0.90	
Pdh Tj = +2°C	2.50 kW	2.50 kW	
COP Tj = +2°C	4.86	3.41	
Cdh Tj = +2 °C	0.90	0.90	
Pdh Tj = +7°C	1.60 kW	1.60 kW	
COP Tj = +7°C	6.34	4.31	
Cdh Tj = +7 °C	0.90	0.90	
Pdh Tj = 12°C	1.50 kW	1.20 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

COP Tj = 12°C	8.15	5.27
Cdh Tj = +12 °C	0.90	0.90
Pdh Tj = Tbiv	4.10 kW	4.20 kW
COP Tj = Tbiv	2.86	1.94
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	3.80 kW	4.10 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.62	1.77
WTOL	55 °C	55 °C
Poff	17 W	17 W
РТО	105 W	105 W
PSB	11 W	11 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.80 kW	0.60 kW
Annual energy consumption Qhe	2046 kWh	2978 kWh