

Page 1 of 4 This information was generated by the HP KEYMARK database on 1 Jul 2022

<u>Login</u>

Summary of	IDEAL LOGIC AIR 10kW	Reg. No.	012-C700133
Certificate Holder			
Name	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT		
Subtype title	IDEAL LOGIC AIR 10kW		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	1.47 kg		
Certification Date	01.07.2022		
Testing basis	EN 14511:2018, EN 14825:2016, EN 12102:2017		



Model: IDEAL LOGIC AIR 10kW

Configure model			
Model name IDEAL LOGIC AIR 10kW			
Application Heating (medium temp)			
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply 1x230V 50Hz		

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	10.30 kW	10.30 kW	
El input	2.10 kW	3.42 kW	
СОР	4.90	3.01	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

Average Climate



This information was generated by the HP KEYMARK database on 1 Jul 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	59 dB(A)	59 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	205 %	146 %	
Prated	10.60 kW	10.20 kW	
SCOP	5.19	3.73	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	9.40 kW	9.00 kW	
$COP Tj = -7^{\circ}C$	3.17	2.27	
Cdh Tj = -7 °C	1.000	1.000	
Pdh Tj = +2°C	5.70 kW	5.50 kW	
COP Tj = +2°C	5.17	3.66	
Cdh Tj = +2 °C	0.990	0.990	
Pdh Tj = $+7^{\circ}$ C	3.70 kW	3.50 kW	
$COPTj = +7^{\circ}C$	6.91	4.91	
Cdh Tj = +7 °C	0.970	0.980	
Pdh Tj = 12°C	4.50 kW	4.40 kW	
	·		

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 1 Jul 2022

COP Tj = 12°C	8.40	6.63
Cdh Tj = +12 °C	0.970	0.980
Pdh Tj = Tbiv	9.40 kW	9.00 kW
COP Tj = Tbiv	3.17	2.27
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	9.10 kW	8.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.84	2.03
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	55 °C	55 °C
Poff	7 W	7 W
РТО	15 W	14 W
PSB	10 W	10 W
РСК	o w	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.50 kW	2.00 kW
Annual energy consumption Qhe	4219 kWh	5655 kWh