

### Page 1 of 4

### This information was generated by the HP KEYMARK database on 7 Jul 2022

#### **Login**

Summary of	Bosch Compress 7000 LW 22	Reg. No.	011-1W0152	
Certificate Holder				
Name	Bosch Thermotechnik GmbH	Bosch Thermotechnik GmbH		
Address	Junkersstraße 20 - 24	Zip	73249	
City	Wernau	Country	Germany	
Certification Body	DIN CERTCO Gesellschaft für Konfo	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Bosch Compress 7000 LW 22	Bosch Compress 7000 LW 22		
Heat Pump Type	Brine/Water			
Refrigerant	R410A	R410A		
Mass of Refrigerant	4.5 kg			



# **Model: Bosch Compress 7000 LW 22**

Configure model			
Model name	Bosch Compress 7000 LW 22		
Application	Heating (medium temp)		
Units	Indoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

### Heating

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow		
Complete power supply failure	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	22.90 kW	23.27 kW	
El input	5.01 kW	7.73 kW	
СОР	4.57	3.01	

## Average Climate



This information was generated by the HP KEYMARK database on 7 Jul 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	57 dB(A)	57 dB(A)	

EN 14825		
	Low temperature	Medium temperature
$\eta_{s}$	207 %	160 %
Prated	21.00 kW	21.00 kW
SCOP	5.38	4.19
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	18.58 kW	18.58 kW
COP Tj = -7°C	4.80	3.31
Pdh Tj = +2°C	11.77 kW	11.78 kW
COP Tj = +2°C	5.54	4.31
Pdh Tj = +7°C	11.76 kW	11.77 kW
COP Tj = +7°C	5.65	4.61
Pdh Tj = 12°C	11.74 kW	11.76 kW
COP Tj = 12°C	5.67	4.88
Pdh Tj = Tbiv	22.90 kW	23.27 kW
COP Tj = Tbiv	4.57	3.01

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 7 Jul 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	22.90 kW	23.27 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.57	3.01
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.00	1.00
WTOL	68 °C	68 °C
Poff	25 W	25 W
PTO	25 W	25 W
PSB	25 W	25 W
PCK	0 W	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	8072 kWh	10349 kWh