

This information was generated by the HP KEYMARK database on 18 Mar 2022

[Login](#)

Summary of	WPF 66	Reg. No.	011-1W0278
Certificate Holder			
Name	STIEBEL ELTRON GmbH & Co KG		
Address	Dr. Stiebel Straße 33	Zip	37603
City	Holzminden	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	WPF 66		
Heat Pump Type	Brine/Water		
Refrigerant	R410A		
Mass of Refrigerant	14.5 kg		
Certification Date	24.01.2019		

Model: WPF 66

Configure model	
Model name	WPF 66
Application	Heating (medium temp)
Units	Indoor + Outdoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 14511-2		
	Low temperature	Medium temperature
Heat output	67.10 kW	62.30 kW
El input	14.23 kW	21.60 kW
COP	4.56	2.82

Average Climate

This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 14825

	Low temperature	Medium temperature
η_s	190 %	131 %
Prated	67.00 kW	62.00 kW
SCOP	4.95	3.48
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	67.20 kW	62.80 kW
COP Tj = -7°C	4.62	2.94
Pdh Tj = +2°C	67.70 kW	64.50 kW
COP Tj = +2°C	4.93	3.44
Pdh Tj = +7°C	68.20 kW	65.50 kW
COP Tj = +7°C	5.25	3.82
Pdh Tj = 12°C	68.70 kW	66.50 kW
COP Tj = 12°C	5.61	4.28
Pdh Tj = Tbiv	67.10 kW	62.30 kW
COP Tj = Tbiv	4.56	2.82
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	67.10 kW	62.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.56	2.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.90	0.90
WTOL	60 °C	60 °C

This information was generated by the HP KEYMARK database on 18 Mar 2022

Poff	0 W	0 W
PTO	7 W	7 W
PSB	7 W	7 W
PCK	99 W	99 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	28022 kWh	37120 kWh

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	63 dB(A)	63 dB(A)
Sound power level outdoor	63 dB(A)	63 dB(A)

Warmer Climate

EN 14825		
	Low temperature	Medium temperature
η_s	190 %	130 %
Prated	67.00 kW	62.00 kW
SCOP	4.95	3.45
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C

This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = +2°C	67.10 kW	62.30 kW
COP Tj = +2°C	4.56	2.82
Pdh Tj = +7°C	67.60 kW	63.70 kW
COP Tj = +7°C	4.86	3.20
Pdh Tj = 12°C	68.40 kW	65.90 kW
COP Tj = 12°C	5.37	3.96
Pdh Tj = Tbiv	67.10 kW	62.30 kW
COP Tj = Tbiv	4.56	2.82
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	67.10 kW	62.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.56	2.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.90	0.90
WTOL	60 °C	60 °C
Poff	0 W	0 W
PTO	7 W	7 W
PSB	7 W	7 W
PCK	99 W	99 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	18119 kWh	24059 kWh

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	63 dB(A)	63 dB(A)
Sound power level outdoor	63 dB(A)	63 dB(A)

Colder Climate

EN 14825		
	Low temperature	Medium temperature
η_s	197 %	136 %
Prated	83.00 kW	78.00 kW
SCOP	5.13	3.60
Tbiv	-15 °C	-15 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	68.00 kW	64.40 kW
COP Tj = -7°C	5.09	3.42
Pdh Tj = +2°C	68.30 kW	65.50 kW
COP Tj = +2°C	5.34	3.81
Pdh Tj = +7°C	68.60 kW	66.30 kW
COP Tj = +7°C	5.55	4.18
Pdh Tj = 12°C	68.70 kW	67.00 kW
COP Tj = 12°C	5.58	4.49

This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = Tbiv	67.80 kW	63.70 kW
COP Tj = Tbiv	4.99	3.21
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	67.10 kW	62.30 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.56	2.82
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.90	0.90
WTOL	60 °C	60 °C
Poff	0 W	0 W
PTO	7 W	7 W
PSB	7 W	7 W
PCK	99 W	99 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	16.03 kW	15.83 kW
Annual energy consumption Qhe	39996 kWh	53447 kWh

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	63 dB(A)	63 dB(A)
Sound power level outdoor	63 dB(A)	63 dB(A)