

This information was generated by the HP KEYMARK database on 7 Jul 2022

[Login](#)

Summary of	VIESSMANN Vitocal 262-A (300 L)	Reg. No.	011-1W0066
Certificate Holder			
Name	Viessmann Faulquemont SAS		
Address	Avenue André Gouy	Zip	F-57380
City	Faulquemont	Country	France
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	VIESSMANN Vitocal 262-A (300 L)		
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)		
Refrigerant	R134a		
Mass of Refrigerant	1.35 kg		

Model: VIESSMANN Vitocal 262-A (300 L) Typ T2E

Configure model	
Model name	VIESSMANN Vitocal 262-A (300 L) Typ T2E
Units	Indoor + Outdoor
Climate zone (for heating)	n/a
Heat Source	n/a
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Domestic Hot Water (DHW)

Average Climate

EN 12102-2	
Sound power level indoor	50 dB(A)
Sound power level outdoor	64 dB(A)

This information was generated by the HP KEYMARK database on 7 Jul 2022

EN 16147	
Declared load profile	XL
Efficiency η_{DHW}	134 %
COP	3.29
Heating up time	11h48min h:min
Standby power input	22.0 W
Reference hot water temperature	52.9 °C
Mixed water at 40°C	394 l

Model: VIESSMANN Vitocal 262-A (300 L) Typ T2E

Configure model	
Model name	VIESSMANN Vitocal 262-A (300 L) Typ T2E
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	n/a
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Domestic Hot Water (DHW)

Average Climate

EN 12102-2	
Sound power level indoor	56 dB(A)

EN 16147	
Declared load profile	XL
Efficiency η_{DHW}	155 %
COP	3.79
Heating up time	8h32 h:min
Standby power input	20.0 W
Reference hot water temperature	52.8 °C
Mixed water at 40°C	409 l

Model: VIESSMANN Vitocal 262-A (300 L) Typ T2H

Configure model	
Model name	VIESSMANN Vitocal 262-A (300 L) Typ T2H
Units	Indoor + Outdoor
Climate zone (for heating)	n/a
Heat Source	n/a
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Domestic Hot Water (DHW)

Average Climate

EN 12102-2	
Sound power level indoor	50 dB(A)
Sound power level outdoor	64 dB(A)

This information was generated by the HP KEYMARK database on 7 Jul 2022

EN 16147	
Declared load profile	XL
Efficiency η_{DHW}	134 %
COP	3.29
Heating up time	11h48min h:min
Standby power input	22.0 W
Reference hot water temperature	52.9 °C
Mixed water at 40°C	394 l

Model: VIESSMANN Vitocal 262-A (300 L) Typ T2H

Configure model	
Model name	VIESSMANN Vitocal 262-A (300 L) Typ T2H
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	n/a
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Domestic Hot Water (DHW)

Average Climate

EN 12102-2	
Sound power level indoor	56 dB(A)

EN 16147	
Declared load profile	XL
Efficiency η_{DHW}	155 %
COP	3.79
Heating up time	8h32 h:min
Standby power input	20.0 W
Reference hot water temperature	52.8 °C
Mixed water at 40°C	409 l

This information was generated by the HP KEYMARK database on 7 Jul 2022