

This information was generated by the HP KEYMARK database on 22 Jun 2022

[Login](#)

Summary of	WPF 7 basic	Reg. No.	011-1W0017
Certificate Holder			
Name	STIEBEL ELTRON GmbH & Co KG		
Address	Dr. Stiebel Straße 33	Zip	37603
City	Holzminden	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	WPF 7 basic		
Heat Pump Type	Brine/Water		
Refrigerant	R410A		
Mass of Refrigerant	2 kg		
Certification Date	25.08.2016		

Model: WPF 7 basic, all climates

Configure model	
Model name	WPF 7 basic, all climates
Application	Heating (low temp)
Units	Indoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2	
	Low temperature
Heat output	7.64 kW
El input	1.70 kW
COP	4.50

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	failed
Starting and operating test	passed

Warmer Climate

This information was generated by the HP KEYMARK database on 22 Jun 2022

EN 12102-1

	Low temperature
Sound power level indoor	55 dB(A)

EN 14825

	Low temperature
η_s	191 %
Prated	8.00 kW
SCOP	4.97
Tbiv	2 °C
TOL	2 °C
Pdh Tj = +2°C	7.60 kW
COP Tj = +2°C	4.49
Cdh Tj = +2 °C	0.90
Pdh Tj = +7°C	7.70 kW
COP Tj = +7°C	4.85
Cdh Tj = +7 °C	0.90
Pdh Tj = 12°C	7.90 kW
COP Tj = 12°C	5.45
Cdh Tj = +12 °C	0.90
Pdh Tj = Tbiv	7.60 kW

This information was generated by the HP KEYMARK database on 22 Jun 2022

COP $T_j = T_{biv}$	4.49
$P_{dh} T_j = TOL$ or $P_{dh} T_j = T_{designh}$ if $TOL < T_{designh}$	7.60 kW
COP $T_j = TOL$ or COP $T_j = T_{designh}$ if $TOL < T_{designh}$	4.49
WTOL	60 °C
Poff	0 W
PTO	78 W
PSB	3 W
PCK	0 W
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Q_{he}	2052 kWh

Colder Climate

EN 12102-1	
	Low temperature
Sound power level indoor	55 dB(A)

EN 14825	
	Low temperature
η_s	200 %
Prated	10.00 kW

This information was generated by the HP KEYMARK database on 22 Jun 2022

SCOP	5.20
Tbiv	-15 °C
TOL	-22 °C
Pdh Tj = -7°C	7.80 kW
COP Tj = -7°C	5.13
Cdh Tj = -7 °C	0.90
Pdh Tj = +2°C	7.90 kW
COP Tj = +2°C	5.42
Cdh Tj = +2 °C	0.90
Pdh Tj = +7°C	7.90 kW
COP Tj = +7°C	5.42
Cdh Tj = +7 °C	0.90
Pdh Tj = 12°C	7.90 kW
COP Tj = 12°C	5.68
Cdh Tj = +12 °C	0.90
Pdh Tj = Tbiv	7.80 kW
COP Tj = Tbiv	5.00
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	5.00
WTOL	60 °C
Poff	0 W

This information was generated by the HP KEYMARK database on 22 Jun 2022

PTO	78 W
PSB	3 W
PCK	0 W
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	1.89 kW
Annual energy consumption Q _{he}	4517 kWh
P _{dh} T _j = -15°C (if TOL<-20°C)	6.80
COP T _j = -15°C (if TOL<-20°C)	2.53
C _{dh} T _j = -15 °C	0.90

Average Climate

EN 12102-1	
	Low temperature
Sound power level indoor	55 dB(A)

EN 14825	
	Low temperature
η_s	192 %
Prated	8.00 kW
SCOP	5.01
T _{biv}	-10 °C

This information was generated by the HP KEYMARK database on 22 Jun 2022

TOL	-20 °C
Pdh Tj = -7°C	7.70 kW
COP Tj = -7°C	4.56
Cdh Tj = -7 °C	0.90
Pdh Tj = +2°C	7.80 kW
COP Tj = +2°C	4.93
Cdh Tj = +2 °C	0.90
Pdh Tj = +7°C	7.80 kW
COP Tj = +7°C	5.31
Cdh Tj = +7 °C	0.90
Pdh Tj = 12°C	7.90 kW
COP Tj = 12°C	5.74
Cdh Tj = +12 °C	0.90
Pdh Tj = Tbiv	7.60 kW
COP Tj = Tbiv	4.49
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.60 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.49
WTOL	60 °C
Poff	0 W
PTO	78 W
PSB	3 W

This information was generated by the HP KEYMARK database on 22 Jun 2022

PCK	0 W
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Q _{he}	3153 kWh

Model: WPF 7 basic, average climates

Configure model	
Model name	WPF 7 basic, average climates
Application	Heating (medium temp)
Units	Indoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	7.64 kW	6.76 kW
El input	1.70 kW	2.67 kW
COP	4.50	2.53

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	failed
Starting and operating test	passed

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	55 dB(A)	55 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	192 %	122 %
Prated	8.00 kW	7.00 kW
SCOP	5.01	3.25
Tbiv	-10 °C	-10 °C
TOL	-20 °C	-10 °C
Pdh Tj = -7°C	7.70 kW	6.80 kW
COP Tj = -7°C	4.56	2.66
Cdh Tj = -7 °C	0.90	0.90
Pdh Tj = +2°C	7.80 kW	7.10 kW
COP Tj = +2°C	4.93	3.19
Cdh Tj = +2 °C	0.90	0.90
Pdh Tj = +7°C	7.80 kW	7.30 kW
COP Tj = +7°C	5.31	3.60
Cdh Tj = +7 °C	0.90	0.90
Pdh Tj = 12°C	7.90 kW	7.50 kW

This information was generated by the HP KEYMARK database on 22 Jun 2022

COP Tj = 12°C	5.74	4.11
Cdh Tj = +12 °C	0.90	0.90
Pdh Tj = Tbiv	7.60 kW	6.80 kW
COP Tj = Tbiv	4.49	2.53
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.60 kW	6.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.49	2.53
WTOL	60 °C	60 °C
Poff	0 W	0 W
PTO	78 W	78 W
PSB	3 W	3 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	3153 kWh	4298 kWh