

Page 1 of 5

This information was generated by the HP KEYMARK database on 21 Jun 2022

Login

Summary of	Bosch Compress 6000 10 LWM	Reg. No.	011-1W0171	
Certificate Holder				
Name	Bosch Thermotechnik GmbH	Bosch Thermotechnik GmbH		
Address	Junkersstraße 20 - 24	Zip	73249	
City	Wernau	Country	Germany	
Certification Body	DIN CERTCO Gesellschaft für Konform	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Bosch Compress 6000 10 LWM	Bosch Compress 6000 10 LWM		
Heat Pump Type	Brine/Water			
Refrigerant	R410A			
Mass of Refrigerant	2.2 kg			



Model: Bosch Compress 6000 10 LWM

Configure model		
Model name	Bosch Compress 6000 10 LWM	
Application	Heating + DHW + low temp	
Units	Indoor	
Climate Zone	n/a	
Reversibility	No	
Cooling mode application (optional)	n/a	

General Data		
Power supply	3x400V 50Hz	
Off-peak product	No	

Heating

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	9.89 kW	9.18 kW	
El input	2.27 kW	3.28 kW	
СОР	4.37	2.80	

Average Climate



This information was generated by the HP KEYMARK database on 21 Jun 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	52 dB(A)	52 dB(A)	

EN 14825		
	Low temperature	Medium temperature
η_{s}	190 %	136 %
Prated	11.00 kW	11.00 kW
SCOP	4.95	3.60
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	9.90 kW	9.30 kW
COP Tj = -7°C	4.74	3.09
Pdh Tj = $+2$ °C	10.00 kW	9.50 kW
COP Tj = +2°C	4.95	3.55
Pdh Tj = +7°C	10.00 kW	9.60 kW
$COPTj = +7^{\circ}C$	5.14	3.98
Pdh Tj = 12°C	10.10 kW	9.80 kW
COP Tj = 12°C	5.34	4.41
Pdh Tj = Tbiv	9.90 kW	9.20 kW
COP Tj = Tbiv	4.63	2.88

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 5 This information was generated by the HP KEYMARK database on 21 Jun 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	9.90 kW	9.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.63	2.88
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.90	0.90
WTOL	62 °C	62 °C
Poff	6 W	6 W
РТО	6 W	6 W
PSB	6 W	6 W
PCK	o w	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.30 kW	1.30 kW
Annual energy consumption Qhe	4672 kWh	6022 kWh

Domestic Hot Water (DHW)

Average Climate





 $$\operatorname{\textit{Page}}\xspace\:5\:\:\text{of}\:5\:$ This information was generated by the HP KEYMARK database on 21 Jun 2022

EN 16147		
Declared load profile	L	
Efficiency ηDHW	89 %	
СОР	2.08	
Heating up time	1:05 h:min	
Standby power input	66.0 W	
Reference hot water temperature	49.6 °C	
Mixed water at 40°C	220	