Summary of	WPF 05, WPF 05 cool, WPC 05, WPC 05 cool	Reg. No.	011-1W0009
Certificate Holder			
Name	STIEBEL ELTRON GmbH & Co KG		
Address	Dr. Stiebel Straße 33	Zip	37603
City	Holzminden	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Name of testing laboratory	VDE Prüf- und Zertifizierungsinstitut		
Subtype title	WPF 05, WPF 05 cool, WPC 05, WPC 05 cool		
Heat Pump Type	Brine/Water		
Refrigerant	R410a		
Mass Of Refrigerant	1.4 kg		
Certification Date	23.08.2016		

Model: WPF 05, average climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	5.82 kW	5.19 kW
El input	1.21 kW	1.85 kW
COP	4.80	2.81
Indoor water flow rate	1.04 m³/h	1.04 m³/h

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	46 dB(A)	46 dB(A)
Sound power level outdoor	0 dB(A)	0 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	205 %	134 %
Prated	6.00 kW	5.00 kW
SCOP	5.32	3.55
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.80 kW	5.30 kW
COP Tj = -7°C	4.87	2.94
Pdh Tj = +2°C	5.90 kW	5.50 kW
COP Tj = +2°C	5.24	3.49
Pdh Tj = +7°C	6.00 kW	5.60 kW
COP Tj = +7°C	5.61	3.92
Pdh Tj = 12°C	6.00 kW	5.70 kW
COP Tj = 12°C	6.03	4.44
Pdh Tj = Tbiv	5.80 kW	5.20 kW

COP Tj = Tbiv	4.81	2.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW	5.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81	2.81
Rated airflow rate	0 m³/h	0 m³/h
Cdh	0.90	0.90
WTOL	65 °C	65 °C
Poff	0 W	0 W
PTO	54 W	54 W
PSB	9 W	9 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2262 kWh	3017 kWh

Warmer Climate

Colder Climate

Model: WPC 05, all climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2	
	Low temperature
Heat output	5.82 kW
El input	1.21 kW
COP	4.80
Indoor water flow rate	1.04 m³/h

Average Climate

EN 12102-1	
	Low temperature
Sound power level indoor	47 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	205 %
Prated	6.00 kW
SCOP	5.32
Tbiv	-10 °C
TOL	-10 °C
Pdh Tj = -7°C	5.80 kW
COP Tj = -7°C	4.87
Pdh Tj = +2°C	5.90 kW
COP Tj = +2°C	5.24
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.61
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.03
Pdh Tj = Tbiv	5.80 kW

COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	2262 kWh

Warmer Climate

EN 12102-1	
	Low temperature
Sound power level indoor	47 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature

η_s	203 %
Prated	6.00 kW
SCOP	5.28
Tbiv	2 °C
TOL	0 °C
Pdh Tj = -7°C	0.00 kW
COP Tj = -7°C	0.00
Pdh Tj = +2°C	5.80 kW
COP Tj = +2°C	4.81
Pdh Tj = +7°C	5.90 kW
COP Tj = +7°C	5.16
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	5.75
Pdh Tj = Tbiv	5.80 kW
COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m^3/h
Cdh	0.90
WTOL	65 °C

Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	1473 kWh

Colder Climate

EN 12102-1	
	Low temperature
Sound power level indoor	47 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	212 %
Prated	7.00 kW
SCOP	5.49
Tbiv	-15 °C
TOL	-22 °C

Pdh Tj = -7°C	5.90 kW
COP Tj = -7°C	5.43
Pdh Tj = +2°C	6.00 kW
COP Tj = +2°C	5.72
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.97
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.01
Pdh Tj = Tbiv	5.90 kW
COP Tj = Tbiv	5.31
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	5.31
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	1.43 kW

Annual energy consumption Qhe	3254 kWh

Model: WPC 05, average climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	5.82 kW	5.19 kW
El input	1.21 kW	1.85 kW
COP	4.80	2.81
Indoor water flow rate	1.04 m³/h	1.04 m³/h

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	47 dB(A)	47 dB(A)
Sound power level outdoor	0 dB(A)	0 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	205 %	134 %
Prated	6.00 kW	5.00 kW
SCOP	5.32	3.55
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.80 kW	5.30 kW
COP Tj = -7°C	4.87	2.94
Pdh Tj = +2°C	5.90 kW	5.50 kW
COP Tj = +2°C	5.24	3.49
Pdh Tj = +7°C	6.00 kW	5.60 kW
COP Tj = +7°C	5.61	3.92
Pdh Tj = 12°C	6.00 kW	5.70 kW
COP Tj = 12°C	6.03	4.44
Pdh Tj = Tbiv	5.80 kW	5.20 kW

COP Tj = Tbiv	4.81	2.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW	5.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81	2.81
Rated airflow rate	0 m³/h	0 m³/h
Cdh	0.90	0.90
WTOL	65 °C	65 °C
Poff	0 W	0 W
PTO	54 W	54 W
PSB	9 W	9 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2262 kWh	3017 kWh

Warmer Climate

Colder Climate

Model: WPF 05, all climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2	
	Low temperature
Heat output	5.82 kW
El input	1.21 kW
COP	4.80
Indoor water flow rate	1.04 m³/h

Average Climate

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	205 %
Prated	6.00 kW
SCOP	5.32
Tbiv	-10 °C
TOL	-10 °C
Pdh Tj = -7°C	5.80 kW
COP Tj = -7°C	4.87
Pdh Tj = +2°C	5.90 kW
COP Tj = +2°C	5.24
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.61
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.03
Pdh Tj = Tbiv	5.80 kW

COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	2262 kWh

Warmer Climate

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature

η_s	203 %
Prated	6.00 kW
SCOP	5.28
Tbiv	2 °C
TOL	0 °C
Pdh Tj = -7°C	0.00 kW
COP Tj = -7°C	0.00
Pdh Tj = +2°C	5.80 kW
COP Tj = +2°C	4.81
Pdh Tj = +7°C	5.90 kW
COP Tj = +7°C	5.16
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	5.75
Pdh Tj = Tbiv	5.80 kW
COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m^3/h
Cdh	0.90
WTOL	65 °C

Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	1473 kWh

Colder Climate

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	212 %
Prated	7.00 kW
SCOP	5.49
Tbiv	-15 °C
TOL	-22 °C

Pdh Tj = -7°C	5.90 kW
COP Tj = -7°C	5.43
Pdh Tj = +2°C	6.00 kW
COP Tj = +2°C	5.72
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.97
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.01
Pdh Tj = Tbiv	5.90 kW
COP Tj = Tbiv	5.31
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	5.31
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	1.43 kW

Annual energy consumption Qhe	3254 kWh

Model: WPF 05 cool, average climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	5.82 kW	5.19 kW
El input	1.21 kW	1.85 kW
COP	4.80	2.81
Indoor water flow rate	1.04 m³/h	1.04 m³/h

Average Climate

EN 12102-1		
	Low temperature	**Medium temperature**
Sound power level indoor	46 dB(A)	46 dB(A)
Sound power level outdoor	0 dB(A)	0 dB(A)

EN 14825		
	Low temperature	**Medium temperature**
η_s	205 %	134 %
Prated	6.00 kW	5.00 kW
SCOP	5.32	3.55
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.80 kW	5.30 kW
COP Tj = -7°C	4.87	2.94
Pdh Tj = +2°C	5.90 kW	5.50 kW
COP Tj = +2°C	5.24	3.49
Pdh Tj = +7°C	6.00 kW	5.60 kW
COP Tj = +7°C	5.61	3.92
Pdh Tj = 12°C	6.00 kW	5.70 kW
COP Tj = 12°C	6.03	4.44
Pdh Tj = Tbiv	5.80 kW	5.20 kW

COP Tj = Tbiv	4.81	2.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW	5.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81	2.81
Rated airflow rate	0 m³/h	0 m³/h
Cdh	0.90	0.90
WTOL	65 °C	65 °C
Poff	0 W	0 W
PTO	54 W	54 W
PSB	9 W	9 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2262 kWh	3017 kWh

Warmer Climate

Colder Climate

Model: WPF 05 cool, all climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2	
	Low temperature
Heat output	5.82 kW
El input	1.21 kW
COP	4.80
Indoor water flow rate	1.04 m³/h

Average Climate

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	205 %
Prated	6.00 kW
SCOP	5.32
Tbiv	-10 °C
TOL	-10 °C
Pdh Tj = -7°C	5.80 kW
COP Tj = -7°C	4.87
Pdh Tj = +2°C	5.90 kW
COP Tj = +2°C	5.24
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.61
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.03
Pdh Tj = Tbiv	5.80 kW

COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	2262 kWh

Warmer Climate

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature

η_s	203 %
Prated	6.00 kW
SCOP	5.28
Tbiv	2 °C
TOL	0 °C
Pdh Tj = -7°C	0.00 kW
COP Tj = -7°C	0.00
Pdh Tj = +2°C	5.80 kW
COP Tj = +2°C	4.81
Pdh Tj = +7°C	5.90 kW
COP Tj = +7°C	5.16
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	5.75
Pdh Tj = Tbiv	5.80 kW
COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m^3/h
Cdh	0.90
WTOL	65 °C

Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	1473 kWh

Colder Climate

EN 12102-1	
	Low temperature
Sound power level indoor	46 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	212 %
Prated	7.00 kW
SCOP	5.49
Tbiv	-15 °C
TOL	-22 °C

Pdh Tj = -7°C	5.90 kW
COP Tj = -7°C	5.43
Pdh Tj = +2°C	6.00 kW
COP Tj = +2°C	5.72
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.97
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.01
Pdh Tj = Tbiv	5.90 kW
COP Tj = Tbiv	5.31
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	5.31
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	1.43 kW

Annual energy consumption Qhe	3254 kWh

Model: WPC 05 cool, average climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2		
	Low temperature	**Medium temperature**
Heat output	5.82 kW	5.19 kW
El input	1.21 kW	1.85 kW
COP	4.80	2.81
Indoor water flow rate	1.04 m³/h	1.04 m³/h

Average Climate

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	47 dB(A)	47 dB(A)
Sound power level outdoor	0 dB(A)	0 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	205 %	134 %
Prated	6.00 kW	5.00 kW
SCOP	5.32	3.55
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.80 kW	5.30 kW
COP Tj = -7°C	4.87	2.94
Pdh Tj = +2°C	5.90 kW	5.50 kW
COP Tj = +2°C	5.24	3.49
Pdh Tj = +7°C	6.00 kW	5.60 kW
COP Tj = +7°C	5.61	3.92
Pdh Tj = 12°C	6.00 kW	5.70 kW
COP Tj = 12°C	6.03	4.44
Pdh Tj = Tbiv	5.80 kW	5.20 kW

COP Tj = Tbiv	4.81	2.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW	5.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81	2.81
Rated airflow rate	0 m³/h	0 m³/h
Cdh	0.90	0.90
WTOL	65 °C	65 °C
Poff	0 W	0 W
PTO	54 W	54 W
PSB	9 W	9 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2262 kWh	3017 kWh

Warmer Climate

Colder Climate

Model: WPC 05 cool, all climates

General Data	
Power supply	3x400V 50Hz

Heating

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2	
	Low temperature
Heat output	5.82 kW
El input	1.21 kW
COP	4.80
Indoor water flow rate	1.04 m³/h

Average Climate

EN 12102-1	
	Low temperature
Sound power level indoor	47 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	205 %
Prated	6.00 kW
SCOP	5.32
Tbiv	-10 °C
TOL	-10 °C
Pdh Tj = -7°C	5.80 kW
COP Tj = -7°C	4.87
Pdh Tj = +2°C	5.90 kW
COP Tj = +2°C	5.24
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.61
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.03
Pdh Tj = Tbiv	5.80 kW

COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	2262 kWh

Warmer Climate

EN 12102-1	
	Low temperature
Sound power level indoor	47 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature

η_s	203 %
Prated	6.00 kW
SCOP	5.28
Tbiv	2 °C
TOL	0 °C
Pdh Tj = -7°C	0.00 kW
COP Tj = -7°C	0.00
Pdh Tj = +2°C	5.80 kW
COP Tj = +2°C	4.81
Pdh Tj = +7°C	5.90 kW
COP Tj = +7°C	5.16
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	5.75
Pdh Tj = Tbiv	5.80 kW
COP Tj = Tbiv	4.81
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.80 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.81
Rated airflow rate	0 m^3/h
Cdh	0.90
WTOL	65 °C

Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	0.00 kW
Annual energy consumption Qhe	1473 kWh

Colder Climate

EN 12102-1	
	Low temperature
Sound power level indoor	47 dB(A)
Sound power level outdoor	0 dB(A)

EN 14825	
	Low temperature
η_s	212 %
Prated	7.00 kW
SCOP	5.49
Tbiv	-15 °C
TOL	-22 °C

Pdh Tj = -7°C	5.90 kW
COP Tj = -7°C	5.43
Pdh Tj = +2°C	6.00 kW
COP Tj = +2°C	5.72
Pdh Tj = +7°C	6.00 kW
COP Tj = +7°C	5.97
Pdh Tj = 12°C	6.00 kW
COP Tj = 12°C	6.01
Pdh Tj = Tbiv	5.90 kW
COP Tj = Tbiv	5.31
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.90 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	5.31
Rated airflow rate	0 m³/h
Cdh	0.90
WTOL	65 °C
Poff	0 W
PTO	54 W
PSB	9 W
PCK	0 W
Supplementary Heater: Type of energy input	electricity
Supplementary Heater: PSUP	1.43 kW

Annual energy consumption Qhe	3254 kWh