

## Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	Buderus Logatherm WPS 22.2 HT	Reg. No.	011-1W0152
Certificate Holder	·		
Name	Bosch Thermotechnik GmbH (Buderus)		
Address	Sophienstraße 30-32	Zip	35576
City	Wetzlar	Country	Germany
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Name of testing laboratory	RISE Research Institutes of Sweden AB		
Subtype title	Buderus Logatherm WPS 22.2 HT		
Heat Pump Type	Brine/Water		
Refrigerant	R410a		
Mass Of Refrigerant	4.5 kg		



This information was generated by the HP KEYMARK database on 17 Dec 2020

## Model: Buderus Logatherm WPS 22.2 HT

General Data	
Power supply	3x400V 50Hz

## Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	22.90 kW	23.27 kW
El input	5.01 kW	7.73 kW
СОР	4.57	3.01
Indoor water flow rate	3.94 m³/h	2.51 m³/h

EN 14511-4		
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed	
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed	
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	

## Average Climate



This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	57 dB(A)	57 dB(A)

EN 14825		
	Low temperature	Medium temperature
$\eta_{s}$	207 %	160 %
Prated	21.00 kW	21.00 kW
SCOP	5.38	4.19
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	18.58 kW	18.58 kW
COP Tj = -7°C	4.80	3.31
Pdh Tj = +2°C	11.77 kW	11.78 kW
COP Tj = +2°C	5.54	4.31
Pdh Tj = +7°C	11.76 kW	11.77 kW
COP Tj = +7°C	5.65	4.61
Pdh Tj = 12°C	11.74 kW	11.76 kW
COP Tj = 12°C	5.67	4.88
Pdh Tj = Tbiv	22.90 kW	23.27 kW
COP Tj = Tbiv	4.57	3.01

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}$4$ of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$ 

Pdh Tj = TOL	22.90 kW	23.27 kW
COP Tj = TOL	4.57	3.01
Cdh	1.00	1.00
WTOL	68 °C	68 °C
Poff	25 W	25 W
РТО	25 W	25 W
PSB	25 W	25 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electric	Electric
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	8072 kWh	10349 kWh