

Page 1 of 4

This information was generated by the HP KEYMARK database on 22 Jun 2022

Login

Summary of	CTC CombiAir 16M	Reg. No.	012-C700078	
Certificate Holder	<u> </u>			
Name	Enertech CTC AB	Enertech CTC AB		
Address	Box 309, Näsvägen	Zip	SE-381 26	
City	Ljungby	Country	Sweden	
Certification Body	RISE CERT	RISE CERT		
Subtype title	CTC CombiAir 16M	CTC CombiAir 16M		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R410A			
Mass of Refrigerant	4 kg	4 kg		
Certification Date	30.10.2020			

This information was generated by the HP KEYMARK database on 22 Jun 2022

Model: CTC CombiAir 16M

Configure model			
Model name CTC CombiAir 16M			
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	7.03 kW	6.38 kW	
El input	1.45 kW	2.04 kW	
СОР	4.85	3.13	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

Average Climate



 $$\operatorname{\textit{Page}}\ 3$$ of 4 This information was generated by the HP KEYMARK database on 22 Jun 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	61 dB(A)	61 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	176 %	134 %	
Prated	14.50 kW	14.00 kW	
SCOP	4.47	3.42	
Tbiv	-8 °C	-8 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	12.90 kW	12.50 kW	
COP Tj = -7°C	2.96	2.01	
Pdh Tj = +2°C	7.90 kW	7.60 kW	
COP Tj = +2°C	4.37	3.29	
Pdh Tj = +7°C	5.10 kW	4.90 kW	
$COP Tj = +7^{\circ}C$	5.58	4.68	
Pdh Tj = 12°C	6.40 kW	6.80 kW	
COP Tj = 12°C	6.99	6.51	
Pdh Tj = Tbiv	13.40 kW	12.70 kW	
COP Tj = Tbiv	2.86	1.95	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 22 Jun 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.50 kW	11.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.71	1.95
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.97	0.98
WTOL	58 °C	58 °C
Poff	2 W	2 W
PTO	25 W	16 W
PSB	15 W	15 W
PCK	20 W	20 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.00 kW	3.00 kW
Annual energy consumption Qhe	6702 kWh	8431 kWh