

Page 1 of 5

This information was generated by the HP KEYMARK database on 22 Jun 2022

Login

Summary of	AUA + G50	Reg. No.	ICIM-PDC-000021-01
Certificate Holder			
Name	Argoclima S.p.A		
Address	Via Alfeno Varo, 35	Zip	25020
City	Alfianello (BS)	Country	Italy
Certification Body	ICIM S.p.A.		
Subtype title	AUA + G50		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410A		
Mass of Refrigerant	1.3 kg		
Certification Date	21.02.2019		

This information was generated by the HP KEYMARK database on 22 Jun 2022

Model: AUAH + AEI1G50EMX

Configure model		
Model name	AUAH + AEI1G50EMX	
Application	Heating + DHW + low temp	
Units	Indoor + Outdoor	
Climate Zone	n/a	
Reversibility	Yes	
Cooling mode application (optional)	n/a	

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	3.95 kW	4.10 kW	
El input	0.97 kW	1.72 kW	
СОР	4.09	2.39	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

Average Climate




 $$\operatorname{\textit{Page}}\ 3$$ of 5 This information was generated by the HP KEYMARK database on 22 Jun 2022

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	46 dB(A)	46 dB(A)
Sound power level outdoor	65 dB(A)	65 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_{s}	151 %	111 %
Prated	2.86 kW	3.41 kW
SCOP	3.85	2.84
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	2.53 kW	3.01 kW
$COPTj = -7^{\circ}C$	2.26	1.75
Cdh Tj = -7 °C	0.900	0.900
Pdh Tj = $+2$ °C	1.51 kW	1.86 kW
$COP Tj = +2^{\circ}C$	3.78	2.78
Cdh Tj = +2 °C	0.900	0.900
Pdh Tj = +7°C	1.02 kW	1.13 kW
COP Tj = +7°C	5.30	3.74
Cdh Tj = +7 °C	0.900	0.900

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com





This information was generated by the HP KEYMARK database on 22 Jun 2022

Pdh Tj = 12°C	0.93 kW	1.31 kW
COP Tj = 12°C	7.02	5.88
Cdh Tj = +12 °C	0.900	0.900
Pdh Tj = Tbiv	2.53 kW	3.01 kW
COP Tj = Tbiv	2.26	1.75
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	2.32 kW	2.07 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.02	1.11
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	55 °C	55 °C
Poff	5 W	5 W
РТО	8 W	8 W
PSB	5 W	5 W
PCK	35 W	35 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.53 kW	1.34 kW
Annual energy consumption Qhe	1534 kWh	2479 kWh

Domestic Hot Water (DHW)

Average Climate





 $$\operatorname{\textit{Page}}\xspace\:5\:\:\text{of}\:5\:$ This information was generated by the HP KEYMARK database on 22 Jun 2022

EN 16147		
Declared load profile	XL	
Efficiency ηDHW	90 %	
СОР	2.22	
Heating up time	5:36 h:min	
Standby power input	45.0 W	
Reference hot water temperature	47.0 °C	
Mixed water at 40°C	364	