

Page 1 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Login

Summary of	Hynea Hybrid Duo Gaz	Reg. No.	012-016
Certificate Holder			
Name	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT	RISE CERT	
Subtype title	Hynea Hybrid Duo Gaz	Hynea Hybrid Duo Gaz	
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410A		
Mass of Refrigerant	1.05 kg		



This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: Hynea Hybrid Duo Gaz 3

Configure model		
Model name	Hynea Hybrid Duo Gaz 3	
Application	Heating (low temp)	
Units	Indoor + Outdoor	
Climate Zone	n/a	
Reversibility	No	
Cooling mode application (optional)	n/a	

General Data		
Power supply 1x230V 50Hz		

Heating

EN 14511-2	
	Low temperature
Heat output	2.80 kW
El input	0.66 kW
СОР	4.25

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

Average Climate

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



$$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1	
	Low temperature
Sound power level indoor	53 dB(A)
Sound power level outdoor	58 dB(A)

EN 14825	
	Low temperature
η_{s}	174 %
Prated	4.00 kW
SCOP	4.42
Tbiv	-7 °C
TOL	-10 °C
Pdh Tj = -7°C	3.70 kW
COP Tj = -7°C	2.60
Pdh Tj = +2°C	2.00 kW
COP Tj = +2°C	4.50
Pdh Tj = +7°C	1.50 kW
COP Tj = +7°C	5.70
Pdh Tj = 12°C	1.60 kW
COP Tj = 12°C	7.60
Pdh Tj = Tbiv	3.70 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

COP Tj = Tbiv	2.60
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	3.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.50
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.90
WTOL	50 °C
Poff	5 W
РТО	20 W
PSB	5 W
PCK	o w
Supplementary Heater: Type of energy input	Electricity
Supplementary Heater: PSUP	0.60 kW
Annual energy consumption Qhe	1912 kWh