

This information was generated by the HP KEYMARK database on 6 Jul 2022

[Login](#)

Summary of	WZSV 42	Reg. No.	041-K001-50
Certificate Holder			
Name	ait-deutschland GmbH		
Address	Industriestr. 3	Zip	95359
City	Kasendorf	Country	Germany
Certification Body	BRE Global Limited		
Subtype title	WZSV 42		
Heat Pump Type	Brine/Water		
Refrigerant	R410A		
Mass of Refrigerant	0.9 kg		
Certification Date	21.06.2022		
Testing basis	Heat Pump Keymark Scheme Rules Rev 09		

Model: alpha innotec - WZSV 42K3M

Configure model	
Model name	alpha innotec - WZSV 42K3M
Application	Heating (medium temp)
Units	Indoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	3.86 kW	3.51 kW
El input	0.89 kW	1.25 kW
COP	4.34	2.81

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 6 Jul 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	192 %	135 %
Prated	3.90 kW	4.20 kW
SCOP	5.01	3.56
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	3.46 kW	3.58 kW
COP Tj = -7°C	4.44	3.04
Cdh Tj = -7 °C	1.000	1.000
Pdh Tj = +2°C	2.07 kW	2.18 kW
COP Tj = +2°C	5.18	3.60
Cdh Tj = +2 °C	1.000	1.000
Pdh Tj = +7°C	1.42 kW	1.48 kW
COP Tj = +7°C	5.59	3.98
Cdh Tj = +7 °C	1.000	1.000
Pdh Tj = 12°C	1.42 kW	1.36 kW

This information was generated by the HP KEYMARK database on 6 Jul 2022

COP Tj = 12°C	5.85	4.72
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	3.86 kW	3.58 kW
COP Tj = Tbiv	4.34	3.04
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	3.86 kW	3.51 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.34	2.81
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	55 °C	55 °C
Poff	12 W	12 W
PTO	44 W	44 W
PSB	12 W	12 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	1610 kWh	2436 kWh

Model: alpha innotec - WZSV 42K3MC

Configure model	
Model name	alpha innotec - WZSV 42K3MC
Application	Heating (medium temp)
Units	Indoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	3.86 kW	3.51 kW
El input	0.89 kW	1.25 kW
COP	4.34	2.81

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 6 Jul 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	192 %	135 %
Prated	3.90 kW	4.20 kW
SCOP	5.01	3.56
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	3.46 kW	3.58 kW
COP Tj = -7°C	4.44	3.04
Cdh Tj = -7 °C	1.000	1.000
Pdh Tj = +2°C	2.07 kW	2.18 kW
COP Tj = +2°C	5.18	3.60
Cdh Tj = +2 °C	1.000	1.000
Pdh Tj = +7°C	1.42 kW	1.48 kW
COP Tj = +7°C	5.59	3.98
Cdh Tj = +7 °C	1.000	1.000
Pdh Tj = 12°C	1.42 kW	1.36 kW

This information was generated by the HP KEYMARK database on 6 Jul 2022

COP Tj = 12°C	5.85	4.72
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	3.86 kW	3.58 kW
COP Tj = Tbiv	4.34	3.04
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	3.86 kW	3.51 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.34	2.81
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	55 °C	55 °C
Poff	12 W	12 W
PTO	44 W	44 W
PSB	12 W	12 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	1610 kWh	2436 kWh

Model: NOVELAN - WSV 4.2K3M

Configure model	
Model name	NOVELAN - WSV 4.2K3M
Application	Heating (medium temp)
Units	Indoor
Climate Zone	n/a
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	3.86 kW	3.51 kW
El input	0.89 kW	1.25 kW
COP	4.34	2.81

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 6 Jul 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	192 %	135 %
Prated	3.90 kW	4.20 kW
SCOP	5.01	3.56
Tbiv	-10 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	3.46 kW	3.58 kW
COP Tj = -7°C	4.44	3.04
Cdh Tj = -7 °C	1.000	1.000
Pdh Tj = +2°C	2.07 kW	2.18 kW
COP Tj = +2°C	5.18	3.60
Cdh Tj = +2 °C	1.000	1.000
Pdh Tj = +7°C	1.42 kW	1.48 kW
COP Tj = +7°C	5.59	3.98
Cdh Tj = +7 °C	1.000	1.000
Pdh Tj = 12°C	1.42 kW	1.36 kW

This information was generated by the HP KEYMARK database on 6 Jul 2022

COP Tj = 12°C	5.85	4.72
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	3.86 kW	3.58 kW
COP Tj = Tbiv	4.34	3.04
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	3.86 kW	3.51 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.34	2.81
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	55 °C	55 °C
Poff	12 W	12 W
PTO	44 W	44 W
PSB	12 W	12 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.70 kW
Annual energy consumption Qhe	1610 kWh	2436 kWh