

Page 1 of 4

This information was generated by the HP KEYMARK database on 18 Mar 2022

Login

Summary of	CTC CombiAir 16M	Reg. No.	012-C700078	
Certificate Holder		'	'	
Name	Enertech CTC AB			
Address	Box 309, Näsvägen	Zip	SE-381 26	
City	Ljungby	Country	Sweden	
Certification Body	RISE CERT			
Subtype title	CTC CombiAir 16M	CTC CombiAir 16M		
Heat Pump Type	Outdoor Air/Water			
Refrigerant	R410A			
Mass of Refrigerant	4 kg			
Certification Date	30.10.2020			



This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: CTC CombiAir 16M

Configure model			
Model name	CTC CombiAir 16M		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	7.03 kW	6.38 kW	
El input	1.45 kW	2.04 kW	
СОР	4.85	3.13	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

Average Climate



This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1		
	Low temperature	Medium temperature
Sound power level outdoor	61 dB(A)	61 dB(A)

EN 14825			
	Low temperature	Medium temperature	
η_{s}	176 %	134 %	
Prated	14.50 kW	14.00 kW	
SCOP	4.47	3.42	
Tbiv	-8 °C	-8 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	12.90 kW	12.50 kW	
COP Tj = -7°C	2.96	2.01	
Pdh Tj = +2°C	7.90 kW	7.60 kW	
COP Tj = +2°C	4.37	3.29	
Pdh Tj = +7°C	5.10 kW	4.90 kW	
$COP Tj = +7^{\circ}C$	5.58	4.68	
Pdh Tj = 12°C	6.40 kW	6.80 kW	
COP Tj = 12°C	6.99	6.51	
Pdh Tj = Tbiv	13.40 kW	12.70 kW	
COP Tj = Tbiv	2.86	1.95	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	12.50 kW	11.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.71	1.95
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.97	0.98
WTOL	58 °C	58 °C
Poff	2 W	2 W
РТО	25 W	16 W
PSB	15 W	15 W
PCK	20 W	20 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.00 kW	3.00 kW
Annual energy consumption Qhe	6702 kWh	8431 kWh