

Page 1 of 4

## This information was generated by the HP KEYMARK database on 18 Mar 2022

Ι.	^		ıi.	n	
ш	U	u	П	H	

Summary of	Bosch Compress 7000 LW 28	Reg. No.	011-1W0153	
Certificate Holder				
Name	Bosch Thermotechnik GmbH			
Address	Junkersstraße 20 - 24	Zip	73249	
City	Wernau	Country	Germany	
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH			
Subtype title	Bosch Compress 7000 LW 28			
Heat Pump Type	Brine/Water			
Refrigerant	R410A			
Mass of Refrigerant	5 kg			



This information was generated by the HP KEYMARK database on 18 Mar 2022

## **Model: Bosch Compress 7000 LW 28**

Configure model			
Model name	Bosch Compress 7000 LW 28		
Application	Heating (medium temp)		
Units	Indoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

## Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	29.30 kW	29.32 kW	
El input	6.42 kW	9.61 kW	
СОР	4.57	3.05	

EN 14511-4			
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed		
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed		
Shutting off the heat transfer medium flow	passed		
Complete power supply failure	passed		

## **Average Climate**



 $$\operatorname{\textit{Page}}\xspace$  3 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	57 dB(A)	57 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
$\eta_{s}$	206 %	162 %	
Prated	28.00 kW	28.00 kW	
SCOP	5.35	4.26	
Tbiv	-10 °C	-10 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	24.77 kW	24.77 kW	
COP Tj = -7°C	4.75	3.49	
Pdh Tj = +2°C	15.28 kW	15.12 kW	
COP Tj = +2°C	5.49	4.32	
Pdh Tj = +7°C	15.29 kW	15.12 kW	
COP Tj = +7°C	5.63	4.66	
Pdh Tj = 12°C	15.31 kW	15.12 kW	
COP Tj = 12°C	5.68	4.95	
Pdh Tj = Tbiv	29.30 kW	29.32 kW	
COP Tj = Tbiv	4.57	3.05	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	29.30 kW	29.32 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	4.57	3.05
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.00	1.00
WTOL	68 °C	68 °C
Poff	25 W	25 W
РТО	25 W	25 W
PSB	25 W	25 W
PCK	o w	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	10797 kWh	13584 kWh