

## $$\operatorname{\textit{Page}}\ 1$$ of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	ATLANTIC GEOLIA 10	Reg. No.	012-C700081
Certificate Holder	<del></del>		<del>'</del>
Name	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000
City	La Roche Sur Yon	Country	France
Certification Body	RISE CERT		·
Name of testing laboratory	RISE		
Subtype title	ATLANTIC GEOLIA 10		
Heat Pump Type	Water/Water		
Refrigerant	R410a		
Mass Of Refrigerant	1.45 kg		
Certification Date	16.10.2020		
Testing basis	HP Keymark Scheme Rules rev 8	HP Keymark Scheme Rules rev 8	



This information was generated by the HP KEYMARK database on 17 Dec 2020

## **Model: ATLANTIC GEOLIA 10**

General Data	
Power supply	1x230V 50Hz

## Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	13.38 kW	11.75 kW
El input	2.48 kW	3.52 kW
СОР	5.38	3.34
Indoor water flow rate	2.31 m³/h	1.27 m³/h

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

## Average Climate



This information was generated by the HP KEYMARK database on 17 Dec 2020

	EN 12102-1		
	Low temperature	Medium temperature	
Sound power level indoor	56 dB(A)	56 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
ης	231 %	177 %	
Prated	15.00 kW	14.00 kW	
SCOP	5.98	4.63	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	13.40 kW	12.40 kW	
COP Tj = -7°C	5.71	3.74	
Cdh	0.99	0.99	
Pdh Tj = +2°C	13.50 kW	12.80 kW	
COP Tj = +2°C	6.03	4.67	
Cdh	0.99	0.99	
Pdh Tj = +7°C	13.60 kW	13.00 kW	
$COPTj = +7^{\circ}C$	6.48	5.29	
Cdh	0.99	0.99	
Pdh Tj = 12°C	13.70 kW	13.30 kW	
Pdh Tj = 12°C	13.70 kW	13.30 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

COP Tj = 12°C	6.68	5.91
Cdh	0.99	0.99
Pdh Tj = Tbiv	13.40 kW	12.40 kW
COP Tj = Tbiv	5.71	3.74
Pdh Tj = TOL	13.30 kW	11.80 kW
COP Tj = TOL	5.27	3.27
WTOL	55 °C	55 °C
Poff	2 W	2 W
РТО	24 W	24 W
PSB	4 W	4 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	ELECTRICITY	ELECTRICITY
Supplementary Heater: PSUP	1.80 kW	1.80 kW
Annual energy consumption Qhe	5525 kWh	6242 kWh