

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

	<u> </u>			
Summary of	Jäspi Inverter M6	Reg. No.	012-C900022	
Certificate Holder	·		-	
Name	Kaukora			
Address	Tuotekatu 11	Zip	FI-21200	
City	Raisio	Country	Finland	
Certification Body	RISE CERT	RISE CERT		
Name of testing laboratory	RISE	RISE		
Subtype title	Jäspi Inverter M6	Jäspi Inverter M6		
Heat Pump Type	Outdoor Air/Water			
Refrigerant	R410a	R410a		
Mass Of Refrigerant	1.5 kg	1.5 kg		
Certification Date	26.03.2020	26.03.2020		
Testing basis	HP Keymark Scheme 2	HP Keymark Scheme 2017		



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: Jäspi Inverter M6

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	2.42 kW	1.57 kW	
El input	0.50 kW	0.76 kW	
СОР	4.85	2.06	
Indoor water flow rate	0.17 m³/h	0.12 m³/h	

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	35 dB(A)	35 dB(A)
Sound power level outdoor	50 dB(A)	50 dB(A)

EN 14825			
	Low temperature	Medium temperature	
η_{s}	188 %	131 %	
Prated	4.80 kW	5.30 kW	
SCOP	4.77	3.35	
Tbiv	-7 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	4.30 kW	4.70 kW	
COP Tj = -7°C	2.60	1.88	
Pdh Tj = +2°C	2.60 kW	2.80 kW	
COP Tj = +2°C	4.84	3.26	
Pdh Tj = +7°C	1.70 kW	1.80 kW	
COP Tj = +7°C	6.91	4.72	
Pdh Tj = 12°C	2.70 kW	2.70 kW	
COP Tj = 12°C	7.72	6.47	
Pdh Tj = Tbiv	4.30 kW	4.70 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}4 of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$

CORTI — This	2.60	1.88
COP Tj = Tbiv	2.00	1.00
Pdh Tj = TOL	3.20 kW	4.10 kW
COP Tj = TOL	2.24	1.77
Cdh	0.98	0.99
WTOL	58 °C	58 °C
Poff	7 W	7 W
РТО	12 W	12 W
PSB	12 W	12 W
PCK	o w	o w
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	1.60 kW	1.20 kW
Annual energy consumption Qhe	2089 kWh	3248 kWh