

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	THERMA V High temperature 3rd Gen 16kW	Reg. No.	011-1W0336
Certificate Holder			
Name	LG Electronics Inc.		
Address	84, Wanam-ro, seongsan-gu	Zip	51554
City	Changwon-si	Country	South Korea
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Name of testing laboratory	TÜV Rheinland Korea Ltd.		
Subtype title	THERMA V High temperature 3rd Gen 16kW		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410a		
Mass Of Refrigerant	3.8 kg		
Certification Date	28.06.2019		



This information was generated by the HP KEYMARK database on 17 Dec 2020

## Model: HU161HA U33, HN1610H NK3

General Data		
Power supply	1x230V 50Hz	

## Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	16.00 kW	14.00 kW	
El input	4.89 kW	5.04 kW	
СОР	3.27	2.78	
Indoor water flow rate	2.76 m³/h	1.51 m³/h	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

## Average Climate



 $$\operatorname{\textit{Page}}\xspace$  3 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	63 dB(A)	63 dB(A)
Sound power level outdoor	63 dB(A)	63 dB(A)

EN 14825		
	Low temperature	Medium temperature
$\eta_{s}$	126 %	117 %
Prated	13.00 kW	11.00 kW
SCOP	3.23	3.01
Tbiv	-10 °C	-10 °C
TOL	-15 °C	-15 °C
Pdh Tj = -7°C	11.90 kW	9.60 kW
COP Tj = -7°C	2.40	2.46
Cdh	0.90	0.90
Pdh Tj = +2°C	7.00 kW	5.90 kW
COP Tj = +2°C	3.30	3.47
Cdh	0.90	0.90
Pdh Tj = +7°C	4.70 kW	3.70 kW
COP Tj = +7°C	4.20	3.00
Cdh	0.90	0.90

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Pdh Tj = 12°C	4.80 kW	4.50 kW
COP Tj = 12°C	3.80	3.60
Cdh	0.90	0.90
Pdh Tj = Tbiv	13.50 kW	10.80 kW
COP Tj = Tbiv	2.10	2.00
Pdh Tj = TOL	13.50 kW	10.80 kW
COP Tj = TOL	2.10	2.00
WTOL	65 °C	65 °C
Poff	60 W	60 W
РТО	60 W	60 W
PSB	60 W	60 W
PCK	o w	o w
Supplementary Heater: Type of energy input	N/A	electric
Supplementary Heater: PSUP	0.00 kW	0.20 kW
Annual energy consumption Qhe	8618 kWh	7424 kWh