

Page 1 of 4

This information was generated by the HP KEYMARK database on 18 Mar 2022

Ι.	^		Πİ	n	
ш	u	ч	п	ш	

Summary of	R32 Monobloc 9kW silent	Reg. No.	011-1W0191	
Certificate Holder				
Name	LG Electronics Inc.	LG Electronics Inc.		
Address	84, Wanam-ro, seongsan-gu	Zip	51554	
City	Changwon-si	Country	South Korea	
Certification Body	DIN CERTCO Gesellschaft für Konfor	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	R32 Monobloc 9kW silent	R32 Monobloc 9kW silent		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R32			
Mass of Refrigerant	2.1 kg	2.1 kg		
Certification Date	15.11.2019	15.11.2019		

This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: HM091MRS U33

Configure model			
Model name	HM091MRS U33		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	Yes		
Cooling mode application (optional)	n/a		

General Data		
Power supply	1x230V 50Hz	
Phase-out Date	03.02.2024	

Heating

EN 14511-2				
Low temperature Medium temperature				
Heat output	9.00 kW	6.00 kW		
El input	1.76 kW	2.14 kW		
СОР	5.10	2.80		

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	0 dB(A)	0 dB(A)	
Sound power level outdoor	57 dB(A)	57 dB(A)	

EN 14825			
	Low temperature	Medium temperature	
η_{s}	184 %	130 %	
Prated	8.00 kW	8.00 kW	
SCOP	4.68	3.33	
Tbiv	-10 °C	-7 °C	
TOL	-15 °C	-15 °C	
Pdh Tj = -7°C	7.60 kW	7.08 kW	
COP Tj = -7°C	3.00	2.00	
Cdh Tj = -7 °C	0.90	0.90	
Pdh Tj = $+2$ °C	4.50 kW	4.31 kW	
COP Tj = +2°C	4.65	3.20	
Cdh Tj = +2 °C	0.90	0.90	
Pdh Tj = +7°C	3.60 kW	3.10 kW	
COP Tj = +7°C	6.00	4.60	
Cdh Tj = +7 °C	0.90	0.90	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 18 Mar 2022

Pdh Tj = 12°C	3.00 kW	2.75 kW
COP Tj = 12°C	8.10	6.71
Cdh Tj = +12 °C	0.90	0.90
Pdh Tj = Tbiv	8.00 kW	7.08 kW
COP Tj = Tbiv	2.50	2.00
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	8.00 kW	6.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.50	1.70
WTOL	65 °C	65 °C
Poff	60 W	60 W
РТО	60 W	60 W
PSB	60 W	60 W
РСК	o w	o w
Supplementary Heater: Type of energy input	n/a	Electricity
Supplementary Heater: PSUP	0.00 kW	2.00 kW
Annual energy consumption Qhe	3533 kWh	4971 kWh