

This information was generated by the HP KEYMARK database on 22 Jun 2022

[Login](#)

Summary of	Split 120	Reg. No.	011-1W0443
Certificate Holder			
Name	Bosch Termotecnologia S.A.		
Address	EN 16 -Km 3.7 - Cacia	Zip	3800-533
City	Aveiro	Country	Portugal
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Split 120		
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)		
Refrigerant	R134a		
Mass of Refrigerant	1.55 kg		
Certification Date	29.03.2021		
Testing basis	HP KEYMARK certification scheme rules rev. 8		

## Model: Bosch Compress CS3000DW 120-1 S

Configure model	
Model name	Bosch Compress CS3000DW 120-1 S
Units	Outdoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	No

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 12102-2</b>	
Sound power level outdoor	61 dB(A)

<b>EN 16147</b>	
Declared load profile	M
Efficiency $\eta_{DHW}$	103 %
COP	2.39
Heating up time	2:47 h:min
Standby power input	31.4 W
Reference hot water temperature	53.8 °C
Mixed water at 40°C	185 l

### Operating test

<b>EN 16147</b>	
Temperature operating range	passed
Safety devices checking test	passed
Condensate draining	passed

## Model: Buderus Logatherm WPTS120.1

Configure model	
Model name	Buderus Logatherm WPTS120.1
Units	Outdoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	No

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 12102-2</b>	
Sound power level outdoor	61 dB(A)

<b>EN 16147</b>	
Declared load profile	M
Efficiency $\eta_{DHW}$	103 %
COP	2.39
Heating up time	2:47 h:min
Standby power input	31.4 W
Reference hot water temperature	53.8 °C
Mixed water at 40°C	185 l

### Operating test

<b>EN 16147</b>	
Temperature operating range	passed
Safety devices checking test	passed
Condensate draining	passed

## Model: e.l.m leblanc Ondéa PAC Split 120-1

Configure model	
Model name	e.l.m leblanc Ondéa PAC Split 120-1
Units	Outdoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Any additional heat sources	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	No

## Domestic Hot Water (DHW)

### Average Climate

<b>EN 12102-2</b>	
Sound power level outdoor	61 dB(A)

<b>EN 16147</b>	
Declared load profile	M
Efficiency $\eta_{DHW}$	103 %
COP	2.39
Heating up time	2:47 h:min
Standby power input	31.4 W
Reference hot water temperature	53.8 °C
Mixed water at 40°C	185 l

### Operating test

<b>EN 16147</b>	
Temperature operating range	passed
Safety devices checking test	passed
Condensate draining	passed