

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	Jäspi Inverter Split 8	Reg. No.	012-SC0805-18
Certificate Holder			
Name	Kaukora	Kaukora	
Address	Tuotekatu 11	Zip	FI-21200
City	Raisio	Country	Finland
Certification Body	RISE CERT	·	
Name of testing laboratory	RISE		
Subtype title	Jäspi Inverter Split 8		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water	
Refrigerant	R410a	R410a	
Mass Of Refrigerant	2.6 kg	2.6 kg	



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: Jäspi Inverter Split 8 + Jäspi Splitbox

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	3.86 kW	3.50 kW	
El input	0.83 kW	1.17 kW	
СОР	4.65	2.99	
Indoor water flow rate	0.66 m³/h	0.37 m³/h	

EN 14511-4	
Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	35 dB(A)	35 dB(A)
Sound power level outdoor	55 dB(A)	55 dB(A)

EN 14825			
	Low temperature	Medium temperature	
η_{s}	172 %	127 %	
Prated	8.20 kW	7.00 kW	
SCOP	4.37	3.25	
Tbiv	-8 °C	-9 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	7.40 kW	6.30 kW	
COP Tj = -7°C	2.92	1.94	
Pdh Tj = +2°C	4.50 kW	3.90 kW	
COP Tj = +2°C	4.30	3.11	
Pdh Tj = +7°C	2.90 kW	2.60 kW	
COP Tj = +7°C	5.41	4.42	
Pdh Tj = 12°C	3.50 kW	3.70 kW	
COP Tj = 12°C	6.51	5.93	
Pdh Tj = Tbiv	7.40 kW	6.60 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}4 of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$

COP Tj = Tbiv	2.86	1.83
Pdh Tj = TOL	6.80 kW	5.90 kW
COP Tj = TOL	2.67	1.86
Cdh	0.96	0.97
WTOL	65 °C	65 °C
Poff	2 W	2 W
РТО	15 W	10 W
PSB	15 W	15 W
PCK	30 W	30 W
Supplementary Heater: Type of energy input	electricity	electricity
Supplementary Heater: PSUP	1.40 kW	1.10 kW
Annual energy consumption Qhe	3882 kWh	4447 kWh