

$$\operatorname{\textit{Page}}\ 1$$ of 7 This information was generated by the HP KEYMARK database on 23 Jun 2022

<u>Login</u>

Summary of	Sphera EVO 2.0 Box 4.1, 5.1	Reg. No.	ICIM-PDC-000156		
Certificate Holder					
Name	Clivet s.p.a.	Clivet s.p.a.			
Address	Via camp lonc 25 c.ap.	Via camp lonc 25 c.ap. Zip I-32032			
City	z.i. Villapaiera - Feltre (BL)	Country	Italy		
Certification Body	ICIM S.p.A.	ICIM S.p.A.			
Subtype title	Sphera EVO 2.0 Box 4.1, 5.1				
Heat Pump Type	Outdoor Air/Water				
Refrigerant	R32	R32			
Mass of Refrigerant	1.65 kg	1.65 kg			
Certification Date	15.04.2022	15.04.2022			
Testing basis	HP KEYMARK certification scheme rules rev. n. 9				



This information was generated by the HP KEYMARK database on 23 Jun 2022

Model: SQKN-YEE 1 BC A + MiSAN-YEE 1 S 4.1

Configure model		
Model name SQKN-YEE 1 BC A + MiSAN-YEE 1 S 4.1		
Application Heating (medium temp)		
Units Indoor + Outdoor		
Climate Zone n/a		
Reversibility Yes		
Cooling mode application (optional) n/a		

General Data		
Power supply	1x230V 50Hz	


Heating

EN 14511-2				
Low temperature Medium temperature				
Heat output	8.30 kW	7.50 kW		
El input	1.56 kW	2.35 kW		
СОР	5.31	3.19		

Average Climate

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	dB(A)	41 dB(A)	
Sound power level outdoor	dB(A)	58 dB(A)	

EN 14825





	Low temperature	Medium temperature
η_{s}	210 %	146 %
Prated	8.08 kW	6.88 kW
SCOP	5.32	3.72
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7° C	7.15 kW	6.09 kW
COP Tj = -7° C	3.30	2.27
Cdh Tj = -7 °C	0.900	0.900
Pdh Tj = $+2$ °C	4.65 kW	3.94 kW
COP Tj = +2°C	5.17	3.56
Cdh Tj = +2 °C	0.900	0.900
Pdh Tj = $+7^{\circ}$ C	2.91 kW	2.52 kW
$COP Tj = +7^{\circ}C$	7.08	4.70
Cdh Tj = +7 °C	0.900	0.900
Pdh Tj = 12°C	1.85 kW	1.72 kW
COP Tj = 12°C	9.46	9.71
Cdh Tj = +12 °C	0.900	0.900
Pdh Tj = Tbiv	7.15 kW	6.09 kW
COP Tj = Tbiv	3.30	2.27
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.42 kW	4.97 kW



$$\operatorname{\textit{Page}}4 of 7 This information was generated by the HP KEYMARK database on 23 Jun 2022

COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.06	1.88
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	65 °C	65 °C
Poff	15 W	15 W
РТО	15 W	15 W
PSB	15 W	15 W
PCK	o w	0 W
Supplementary Heater: Type of energy input	n/a	n/a
Supplementary Heater: PSUP	1.66 kW	1.91 kW
Annual energy consumption Qhe	3141 kWh	3824 kWh

This information was generated by the HP KEYMARK database on 23 Jun 2022

Model: SQKN-YEE 1 BC A + MiSAN-YEE 1 S 5.1

Configure model		
Model name SQKN-YEE 1 BC A + MiSAN-YEE 1 S 5.1		
Application Heating (medium temp)		
Units Indoor + Outdoor		
Climate Zone n/a		
Reversibility Yes		
Cooling mode application (optional) n/a		

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2				
Low temperature Medium temperature				
Heat output	10.09 kW	9.60 kW		
El input	2.01 kW	3.10 kW		
СОР	5.01	3.10		

Average Climate

EN 12102-1				
	Low temperature	Medium temperature		
Sound power level indoor	dB(A)	41 dB(A)		
Sound power level outdoor	dB(A)	60 dB(A)		

EN 14825





This information was generated by the HP KEYMARK database on 23 Jun 2022

	Low temperature	Medium temperature
η_{s}	208 %	146 %
Prated	9.55 kW	8.57 kW
SCOP	5.27	3.73
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7° C	8.45 kW	7.58 kW
COP Tj = -7°C	3.18	2.02
Cdh Tj = -7 °C	0.900	0.900
Pdh Tj = $+2$ °C	5.23 kW	4.44 kW
COP Tj = +2°C	5.03	3.63
Cdh Tj = +2 °C	0.900	0.900
Pdh Tj = $+7^{\circ}$ C	3.47 kW	2.92 kW
$COPTj = +7^{\circ}C$	7.33	4.95
Cdh Tj = +7 °C	0.900	0.900
Pdh Tj = 12°C	1.96 kW	1.74 kW
COP Tj = 12°C	9.94	9.87
Cdh Tj = +12 °C	0.900	0.900
Pdh Tj = Tbiv	8.45 kW	7.58 kW
COP Tj = Tbiv	3.18	2.02
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.38 kW	5.46 kW



$$\operatorname{\textit{Page}}\ 7$$ of 7 This information was generated by the HP KEYMARK database on 23 Jun 2022

COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.97	1.87
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	65 °C	65 °C
Poff	15 W	15 W
РТО	15 W	15 W
PSB	15 W	15 W
PCK	o w	o w
Supplementary Heater: Type of energy input	n/a	n/a
Supplementary Heater: PSUP	2.17 kW	3.11 kW
Annual energy consumption Qhe	3747 kWh	4749 kWh