

Page 1 of 7

This information was generated by the HP KEYMARK database on 23 Jun 2022

Login

Summary of	Bosch CS5000AW 38 O	Reg. No.	40054438	
Certificate H	Certificate Holder			
Name	Bosch Thermotechnik GmbH			
Address	Junkersstraße 20 - 24 Zip 73249			
City	Wernau	Country	Germany	
Certification Body	VDE Prüf- und Zertifizierungsinstitut GmbH			
Subtype title	Bosch CS5000AW 38 O			
Heat Pump Type	Outdoor Air/Water			
Refrigerant	R407c			
Mass of Refrigerant	15.7 kg			
Certification Date	ion 14.12.2021			
Testing basis	DIN EN 14511-1:2019-07; EN 14511-1:2018 DIN EN 14511-2:2019-07; EN 14511-2:2018 DIN EN 14511-3:2019-07; EN 14511-3:2018 DIN EN 14511-4:2019-07; EN 14511-4:2018 DIN EN 14825:2019-07; EN 14825:2018 DIN EN 12102-1: 2018-02; EN 12102-1:2017			



This information was generated by the HP KEYMARK database on 23 Jun 2022

Model: Bosch CS5000AW 38 O

Configure model		
Model name	Bosch CS5000AW 38 O	
Application	Heating (medium temp)	
Units	Outdoor	
Climate Zone	n/a	
Reversibility	No	
Cooling mode application (optional)	n/a	

General Data		
Power supply	3x400V 50Hz	

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	35.40 kW	31.70 kW
El input	7.89 kW	10.00 kW
СОР	4.48	3.16

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 7 This information was generated by the HP KEYMARK database on 23 Jun 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	72 dB(A)	72 dB(A)	

EN 14825		
	Low temperature	Medium temperature
η_s	154 %	130 %
Prated	36.00 kW	36.00 kW
SCOP	3.91	3.33
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	38.10 kW	38.10 kW
COP Tj = -7°C	3.02	2.41
Cdh Tj = -7 °C	1.000	1.000
Pdh Tj = +2°C	27.50 kW	26.50 kW
COP Tj = +2°C	3.89	3.30
Cdh Tj = +2 °C	1.000	1.000
Pdh Tj = +7°C	35.20 kW	33.80 kW
$COP Tj = +7^{\circ}C$	4.79	4.19
Cdh Tj = +7 °C	1.000	1.000
Pdh Tj = 12°C	41.30 kW	39.70 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 7 This information was generated by the HP KEYMARK database on 23 Jun 2022

COP Tj = 12°C	5.41	4.76
Cdh Tj = +12 °C	1.000	1.000
Pdh Tj = Tbiv	35.60 kW	36.00 kW
COP Tj = Tbiv	2.85	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	35.60 kW	36.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.85	2.22
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	60 °C	60 °C
Poff	30 W	30 W
РТО	29 W	29 W
PSB	30 W	30 W
PCK	95 W	95 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.42 kW	1.00 kW
Annual energy consumption Qhe	19007 kWh	16840 kWh



This information was generated by the HP KEYMARK database on 23 Jun 2022

Model: Bosch CS5000AW 38 OR

Configure model		
Model name	Bosch CS5000AW 38 OR	
Application	Heating (medium temp)	
Units	Outdoor	
Climate Zone	n/a	
Reversibility	Yes	
Cooling mode application (optional)	n/a	

General Data		
Power supply	3x230V 50Hz	

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	35.40 kW	31.70 kW
El input	7.89 kW	10.00 kW
СОР	4.48	3.16

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate



This information was generated by the HP KEYMARK database on 23 Jun 2022

EN 12102-1				
	Low temperature	Medium temperature		
Sound power level outdoor	72 dB(A)	72 dB(A)		

EN 14825			
	Low temperature	Medium temperature	
η_{s}	157 %	133 %	
Prated	36.00 kW	36.00 kW	
SCOP	4.01	3.40	
Tbiv	-10 °C	-10 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	38.10 kW	39.00 kW	
COP Tj = -7°C	3.02	2.41	
Cdh Tj = -7 °C	1.000	1.000	
Pdh Tj = +2°C	27.50 kW	26.50 kW	
COP Tj = +2°C	3.89	3.30	
Cdh Tj = +2 °C	1.000	1.000	
Pdh Tj = +7°C	35.20 kW	33.80 kW	
COP Tj = +7°C	4.79	4.19	
Cdh Tj = +7 °C	1.000	1.000	
Pdh Tj = 12°C	41.30 kW	39.70 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 7 of 7 This information was generated by the HP KEYMARK database on 23 Jun 2022

COP Tj = 12°C	5.41	4.76
Cdh Tj = +12 °C	1.000	1.000
Pdh Tj = Tbiv	35.60 kW	36.00 kW
COP Tj = Tbiv	2.85	2.22
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	35.60 kW	35.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.85	2.22
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1.000	1.000
WTOL	60 °C	60 °C
Poff	30 W	30 W
РТО	29 W	29 W
PSB	30 W	30 W
РСК	95 W	95 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.42 kW	1.00 kW
Annual energy consumption Qhe	18548 kWh	16564 kWh