

# $$\operatorname{\textit{Page}}\ 1$$ of 4 This information was generated by the HP KEYMARK database on 30 Jun 2022

#### <u>Login</u>

Summary of	Atlantic Ixtra M 15 Tri	Reg. No.	012-C700149	
Certificate Holder				
Name	Groupe Atlantic	Groupe Atlantic		
Address	44 boulevard des Etats-Unis	Zip	85000	
City	La Roche Sur Yon	Country	France	
Certification Body	RISE CERT	RISE CERT		
Subtype title	Atlantic Ixtra M 15 Tri	Atlantic Ixtra M 15 Tri		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R452B	R452B		
Mass of Refrigerant	2.75 kg			
Certification Date	30.06.2022			
Testing basis	EN 14511:2018, EN 14825:2016, EN	EN 14511:2018, EN 14825:2016, EN 12102:2017		

This information was generated by the HP KEYMARK database on 30 Jun 2022

### **Model: Atlantic Ixtra M 15 Tri**

Configure model			
Model name	Atlantic Ixtra M 15 Tri		
Application	Heating (medium temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	No		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

#### Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	8.50 kW	12.90 kW	
El input	1.77 kW	4.31 kW	
СОР	4.79	2.99	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

## Average Climate



This information was generated by the HP KEYMARK database on 30 Jun 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level outdoor	54 dB(A)	54 dB(A)	

EN 14825		
	Low temperature	Medium temperature
$\eta_{s}$	177 %	131 %
Prated	13.50 kW	13.30 kW
SCOP	4.51	3.36
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	11.90 kW	11.80 kW
COP Tj = -7°C	3.04	2.24
Cdh Tj = -7 °C	0.970	0.980
Pdh Tj = +2°C	7.30 kW	7.20 kW
COP Tj = +2°C	4.70	3.38
Cdh Tj = +2 °C	0.970	0.980
Pdh Tj = +7°C	8.60 kW	8.30 kW
$COP Tj = +7^{\circ}C$	5.55	4.24
Cdh Tj = +7 °C	0.970	0.980
Pdh Tj = 12°C	10.10 kW	9.80 kW

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 30 Jun 2022

COP Tj = 12°C	6.53	5.06
Cdh Tj = +12 °C	0.970	0.980
Pdh Tj = Tbiv	11.90 kW	11.80 kW
COP Tj = Tbiv	3.09	2.24
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	11.10 kW	11.20 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.86	2.07
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.970	0.980
WTOL	60 °C	60 °C
Poff	18 W	18 W
РТО	48 W	32 W
PSB	20 W	20 W
PCK	o w	o w
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.40 kW	2.10 kW
Annual energy consumption Qhe	6187 kWh	8179 kWh