

Page 1 of 6

This information was generated by the HP KEYMARK database on 18 Mar 2022

<u>Login</u>

Summary of	i-SHWAK V4 08	Reg. No.	ICIM-PDC-000077-00	
Certificate Holder				
Name	Advantix S.p.A.	Advantix S.p.A.		
Address	Via San Giuseppe Lavoratore, 24	Zip	37040	
City	Arcole Verona	Country	Italy	
Certification Body	ICIM S.p.A.	ICIM S.p.A.		
Subtype title	i-SHWAK V4 08			
Heat Pump Type	Outdoor Air/Water			
Refrigerant	R410A			
Mass of Refrigerant	2.2 kg			
Certification Date	26.05.2020			
Testing basis	HP KEYMARK certification scheme rules rev. no. 7			



This information was generated by the HP KEYMARK database on 18 Mar 2022

Model: i-SHWAK V4 08

Configure model		
Model name	i-SHWAK V4 08	
Application	Heating (medium temp)	
Units	Indoor + Outdoor	
Climate Zone	n/a	
Reversibility	Yes	
Cooling mode application (optional)	+7°C/12°C	

General Data		
Power supply	1x230V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	8.01 kW	6.89 kW	
El input	1.89 kW	3.09 kW	
СОР	4.24	2.23	

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 6 This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1			
	Low temperature	Medium temperature	
Sound power level indoor	35 dB(A)	35 dB(A)	
Sound power level outdoor	64 dB(A)	64 dB(A)	

EN 14825		
	Low temperature	Medium temperature
η_{s}	155 %	124 %
Prated	6.00 kW	5.00 kW
SCOP	3.94	3.17
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.50 kW	5.00 kW
COP Tj = -7°C	2.62	1.72
Cdh Tj = -7 °C	1.00	1.00
Pdh Tj = +2°C	3.40 kW	3.30 kW
COP Tj = +2°C	4.19	3.10
Cdh Tj = +2 °C	1.00	1.00
Pdh Tj = +7°C	3.60 kW	4.00 kW
COP Tj = +7°C	4.39	4.42
Cdh Tj = +7 °C	1.00	1.00

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 6 This information was generated by the HP KEYMARK database on 18 Mar 2022

	· · · · · · · · · · · · · · · · · · ·	
Pdh Tj = 12°C	3.70 kW	4.40 kW
COP Tj = 12°C	5.12	6.18
Cdh Tj = +12 °C	1.00	1.00
Pdh Tj = Tbiv	5.50 kW	5.00 kW
COP Tj = Tbiv	2.62	1.72
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.10 kW	4.40 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.33	1.44
WTOL	39 °C	39 °C
Poff	0 W	0 W
РТО	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	n/a	n/a
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2216 kWh	2493 kWh

Cooling





This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 14511-2		
	+7°C/+12°C	
El input	2.11 kW	
Cooling capacity	6.12	
EER	2.90	

EN 14825





This information was generated by the HP Kt	THE TO MALE TO MALE TO MALE TO THE TOTAL TOTAL TO THE TOTAL TO THE TOTAL TO THE TOTAL TOTAL TO THE TOTAL TO T
	+7°C/+12°C
Pdesignc	6.12 kW
SEER	3.84
Pdc Tj = 35°C	6.12 kW
EER Tj = 35°C	2.90
Pdc Tj = 30°C	4.51 kW
EER Tj = 30°C	3.88
Cdc	1.0
Pdc Tj = 25°C	3.40 kW
EER Tj = 25°C	4.09
Cdc	1.0
Pdc Tj = 20°C	3.68 kW
EER Tj = 20°C	4.92
Cdc	1.0
Poff	12 W
РТО	0 W
PSB	12 W
PCK	0 W
Annual energy consumption Qce	558 kWh